

3M UK PLC
3M CENTRE, CAIN RD,
BRACKNELL, BERKSHIRE, RG12 8HT
Tel: 01344 858000

3M IRELAND
3M HOUSE, ADELPHI CENTRE,
DUN LAOGHAIRE, CO. DUBLIN
Tel: 01 2803555

=====

MATERIAL SAFETY DATA SHEET

=====

Document id : 18-7883-4 Issue date : 13/05/2005
Version : 3.00 Supersedes date : 10/03/2005

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Tradename:
08861 BODY SCHUTZ COATING

3M Product ID:
XS-0034-9152-8

2 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient name and classification	CAS number	Percentage
LIMESTONE	1317-65-3	15 - 40
HYDROTREATED LIGHT NAPHTHA (PETROLEUM)	64742-49-0	15 - 40
EU Hazard Symbols and Risk Phrases: EU - Adaptation 22 (T; R:Carc.Cat.2;45-65) EU - Additional Vendor Classification(F,Xi, N; R:11-38-51/53-67)		
OXIDISED PETROLEUM ASPHALT	64742-93-4	15 - 40
LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM)	64742-95-6	3 - 7
EU Hazard Symbols and Risk Phrases: EU - Adaptation 22 (T; R:Carc.Cat.2;45-65) EU - Additional Vendor Classification(Xi, N; R:10-37-51/53-66-67)		
BIS(HYDROGENATED TALLOW ALKYL)DIMETHYL AMMONIUM SALTS WITH BENTONITE	68953-58-2	1 - 5
METHYL ALCOHOL	67-56-1	Less Than 3
EU Hazard Symbols and Risk Phrases: EU - Adaptation 28 (F,T; R:11-23-24-25-39/23-39/24-39/25) EINECS No: 2006596		
STYRENE-ISOPRENE COPOLYMER	25038-32-8	Less Than 3
TOLUENE	108-88-3	Less Than 3
EU Hazard Symbols and Risk Phrases: EU - Adaptation 29 (F,Xi, Xn; R:11-38-48/20-Repr.Cat.3;63-65-67)		

3 HAZARDS IDENTIFICATION

Critical hazards:
Dangerous to environment. Irritant. Highly Flammable.
Irritating to skin. Vapours may cause drowsiness and
dizziness. Toxic to aquatic organisms. May cause long-term
adverse effects in the aquatic environment.

4 FIRST-AID MEASURES

Eye Contact:

Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact:

Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and shoes before reuse.

Inhalation:

Remove person to fresh air. If signs/symptoms develop, get medical attention.

Ingestion:

Do not induce vomiting. Get immediate medical attention. Give victim two glasses of water. Never give anything by mouth to an unconscious person.

5 FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

Exposure Hazards:

Closed containers exposed to heat from fire may build pressure and explode. Vapours may travel long distances along the ground or floor to an ignition source and flash back.

Hazardous Decomposition:

Aldehydes, Ketones, Hydrocarbons, Methane, Toxic vapours, Gases or particulates, Carbon Monoxide, Carbon Dioxide.

Fire-Fighting Procedures:

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Refer to other sections of this Material Safety Data Sheet for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

Methods for Cleaning up:

For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Contain spill. Cover spill area with a fire-extinguishing foam. An aqueous film forming foam (AFFF) is recommended. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and MSDS. Collect the resulting residue containing solution. Place in a suitable metal container. Dispose of collected material as soon as possible.

7 HANDLING AND STORAGE

Incompatible Materials/Conditions:

Store away from acids. Store away from heat. Store out of direct sunlight. Store away from oxidising agents.

Ventilation:

Keep container in a well-ventilated area.

Fire Prevention:

Ground containers securely when transferring contents. Wear low static or properly grounded shoes. Do not spray near flames or sources of ignition. Extremely flammable liquid and vapour.

Explosion Prevention:

Flammable liquid and vapour. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition.

Static Prevention:

Avoid static discharge.

Precautions for Safe Handling:

Keep container tightly closed. For industrial or professional use only. Avoid contact with oxidising agents.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection:

Avoid eye contact with vapours, mists, or spray. The following should be worn alone or in combination, as appropriate to prevent eye contact: Indirect vented goggles.

Hand Protection:

The following glove material(s) are recommended:
Fluoroelastomer.

Skin Protection:

Avoid skin contact.

Respiratory Protection:

Avoid inhalation of vapours, mists or spray. Select one of the following approved respirators based on airborne concentration of contaminants and in accordance with regulations: Fullface air-purifying respirator with organic vapour cartridges and

particulate prefilters. Fullface supplied-air respirator,

Ingestion:

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

Recommended Ventilation:

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapour, or spray. If ventilation is not adequate, use respiratory protection equipment.

Exposure Limits:

LIMESTONE (1317-65-3)

HSE WEL TWA: 10 mg/m³ Total inhalable dust; 4 mg/m³

Respirable dust OES

LIGHT AROMATIC SOLVENT NAPHTHA (PETROLEUM) (64742-95-6)

CMRG TWA Exposure Limit: 50 ppm 245 mg/m³

METHYL ALCOHOL (67-56-1)

HSE WEL TWA: 200 ppm; 266 mg/m³ skin OES

HSE WEL STEL: 250 ppm; 333 mg/m³ skin OES

EEC Exposure Limit 200 ppm; 260 mg/m³

TOLUENE (108-88-3)

HSE WEL TWA: 50 ppm; 191 mg/m³ skin OES

HSE WEL STEL: 150 ppm; 574 mg/m³ skin OES

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odour: Black liquid, with turpentine odour.

pH: Not determined

Boiling point/boiling range: 80 C

Melting point/melting range: Not determined

Flash point: -10 C

Autoflammability: 200 C

Vapour pressure: 61 mbar

Water Solubility: Not determined

Specific gravity: Not determined

Vapour density: Not determined

Viscosity: 42 sec DETAILS: DIN53211

Percent Volatile: 44.46 %

10 STABILITY AND REACTIVITY

Conditions to Avoid:

Heat. Sparks and/or Flames. Temperatures above the boiling point.

Materials to Avoid:

None known.

Hazardous Decomposition:

Hazardous polymerisation will not occur. Stable.

11 TOXICOLOGICAL INFORMATION

Effects from Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Effects from Skin Contact:

May be absorbed through skin and cause target organ effects.
Moderate Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

Effects from Inhalation:

May be absorbed following inhalation and cause target organ effects. Upper Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Prolonged or repeated exposure may cause: Lung Effects: Signs/symptoms may include difficulty breathing, cough, wheezing, weakness, increased heart rate, bluish colored skin (cyanosis), sputum production and changes in lung function tests.

Effects from Ingestion:

May be absorbed following ingestion and cause target organ effects. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, nausea, diarrhoea and vomiting.

Reproductive Effects:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Other Effects and Information:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice. Central Neuropathy: Signs/symptoms may include irritability, memory impairment, personality changes, sleep disorders, and decreased ability to concentrate. Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

12 ECOLOGICAL INFORMATION

Ecotoxicity Data:

Not determined.

Ecofate Data:

Not determined.

Special statements for 2001/58/EC:

One or more components of this product have significant known or predicted environmental hazards, but a conservative assessment indicates a low environmental risk. Intended use and proper disposal are unlikely to cause the environmentally hazardous component(s) to enter the environment in quantities or by routes that could cause the adverse environmental impacts. Use of this product is expected to result in the release of volatile organic compounds (VOCs) to the

atmosphere. Regulations may restrict the release of VOCs because they contribute to the formation of smog and, to a lesser extent, to the formation of global warming gases. Releases should be minimized to the extent possible. Regulatory definitions for VOCs vary.

Other Effects and Information:

Take precautions to prevent direct release of this product to the environment.

13 DISPOSAL CONSIDERATIONS

Product as Sold:

Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

Special Instructions:

Since regulations vary, consult applicable regulations or authorities before disposal.

14 TRANSPORT INFORMATION

UN NUMBER:

UN number: UN 1139

UK ROAD/SEA FREIGHT (IMO) CLASSIFICATION:

Substance Identification Number: UN 1139

Class: 3

Packing Group: II

Proper Shipping Name: Coating solution.

ADR/RID CLASSIFICATION:

Class: 3

ADR classification: F 1

ICAO/IATA CLASSIFICATION:

Class: 3

Sub-Risk: Not applicable

Packing Group: II

Proper Shipping Name: Coating solution

15 REGULATORY INFORMATION

Disclosable Ingredients:

HYDROTREATED LIGHT NAPHTHA (PETROLEUM)

Symbol(s):

(Xi) St. Andrew's Cross (Irritant). (F) Flame (Highly Flammable). (N) Dangerous to environment.

Risk Phrases:

(R11) Highly Flammable. (R38) Irritating to skin. (R67) Vapours may cause drowsiness and dizziness. (51/53) Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Safety Phrases:

Keep away from sources of ignition - No Smoking. Do not breathe vapour or spray. Use only in well ventilated areas. Avoid contact with the skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with plenty of water. If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label. Avoid release to the environment. Refer to special instructions/safety data sheets. Keep out of the reach of children.

16 OTHER INFORMATION

Regulatory Information: The following UK Regulations as amended may affect the product as supplied: The Chemicals (Hazard Information and Packaging for supply) Regulations, as amended. The Carriage of Dangerous Goods (Classification, Packaging and Labelling) and use of Transportable Pressure Receptacles Regulations 1996, as amended. Carriage of Dangerous Goods by Road regulations, 1996, as amended. The Control of Substances Hazardous to Health Regulations 1999 as amended. The Special Waste Regulations 1996, as amended. The Environmental Protection Act, 1990 The Health and Safety at Work Act, 1974.

Reissue date/Reason for reissue.

Updated sections 2, 10, 15.

Intended Use of Product:

Protective coating.

The information on this Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.