



Safety Data Sheet

Copyright, 2011, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	24-5519-4	Version number:	2.00
Revision date:	16/03/2011	Supersedes date:	14/04/2009
Transportation version number:	1.00 (16/03/2011)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M 08868 High Quality Anti-Chip Coating, Black

3M Product identification numbers

DS-2729-9113-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Anti-corrosion and anti-gravel coating.

1.3. Details of the supplier of the substance or mixture

Address: 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.

E Mail: tox.uk@mmm.com

Website: www.3M.com/uk

1.4. Emergency telephone number

+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive

Indication of danger

Irritant.

Harmful.

Flammable

2.2. Label elements

3M 08868 High Quality Anti-Chip Coating, Black**Dangerous substances(67/548/EEC)/preparations(1999/45/EC) directive****Symbols**

Xn Harmful.

Contains:

Xylene

Risk phrasesR10 Flammable.
R20/21 Harmful by inhalation and in contact with skin.
R38 Irritating to skin.**Safety phrases**S51 Use only in well ventilated areas.
S23C Do not breathe vapour or spray.
S36/37 Wear suitable protective clothing and gloves.**Special provisions concerning the labelling of certain substances**

Contains methyl ethyl ketone oxime. May produce an allergic reaction.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	EU Inventory	% by Wt	Classification
Xylene	1330-20-7	EINECS 215-535-7	25 - 50	Xn:R20-21; Xi:R38; R10 - Nota C (EU) Flam. Liq. 3, H226; Acute Tox. 4, H332; Acute Tox. 4, H312; Skin Irrit. 2, H315 - Nota C (CLP)
Limestone	1317-65-3	EINECS 215-279-6	25 - 50	
Alkyd resin	68459-31-4		10 - 25	
Poly(vinyl chloride-co-isobutyl vinyl ether)	25154-85-2		1 - 5	
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	EINECS 273-219-4	1 - 5	
Ethylbenzene	100-41-4	EINECS 202-849-4	1 - 5	F:R11; Xn:R20 (EU) Flam. Liq. 2, H225; Acute Tox. 4, H332 (CLP)
Carbon black	1333-86-4	EINECS 215-609-9	1 - 5	
2-Butanone oxime	96-29-7	EINECS 202-496-6	< 1	Carc.Cat.3:R40; Xn:R21; Xi:R41; R43 (EU)

3M 08868 High Quality Anti-Chip Coating, Black

				Acute Tox. 4, H312; Eye Dam. 1, H318; Skin Sens. 1, H317; Carc. 2, H351 (CLP)
Synthetic amorphous silica, fumed, crystalline free	112945-52-5		< 1	
Lecithin	8002-43-5	EINECS 232-307-2	< 1	

Please see section 16 for the full text of any R phrases and H statements referred to in this section

Please refer to section 15 for the any applicable Notas that have been applied to the above components

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures**4.1. Description of first aid measures****Eye contact**

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Extinguishing media**

In case of fire: Use a fire fighting agent suitable for flammable liquids or gases such as dry chemical or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Evacuate area. Refer to

3M 08868 High Quality Anti-Chip Coating, Black

other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible using non-sparking tools. Collect as much of the spilled material as possible. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Seal the container. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam (AFFF) is recommended.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Use personal protective equipment (eg. gloves, respirators...) as required. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ventilating/lighting/equipment. Wear low static or properly grounded shoes. Avoid eye contact. Vapours may travel long distances along the ground or floor to an ignition source and flash back. Do not breathe dust/fume/gas/mist/vapours/spray. For industrial or professional use only. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	Health and Safety Comm. (UK)	TWA:441 mg/m ³ (100 ppm);STEL:552 mg/m ³ (125 ppm)	Skin Notation
Silica, amorphous	112945-52-5	Health and Safety Comm. (UK)	TWA(as inhalable dust):6 mg/m ³ ;TWA(as respirable dust):2.4 mg/m ³	
Limestone	1317-65-3	Health and Safety Comm. (UK)	TWA(as inhalable dust):10 mg/m ³ ;TWA(as respirable dust):4 mg/m ³ ;TWA(Inhalable):10 mg/m ³ ;TWA(respirable):4	

3M 08868 High Quality Anti-Chip Coating, Black

Xylene	1330-20-7	Health and Safety Comm. (UK)	mg/m ³ TWA:220 mg/m ³ (50 ppm);STEL:441 mg/m ³ (100 ppm)	Skin Notation
Carbon black	1333-86-4	Health and Safety Comm. (UK)	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³	

Health and Safety Comm. (UK) : UK Health and Safety Commission

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use explosion-proof ventilation equipment. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Wear protective gloves and eye/face protection. Wear eye/face protection. The following eye protection(s) are recommended: Indirect vented goggles.

Skin/hand protection

Wear protective gloves. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

Select one of the following approved respirators based on airborne concentration of contaminants and in accordance with regulations:

Half facepiece or fullface air-purifying respirator with organic vapour cartridges and P2 particulate prefilters.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Appearance/Odour	Black; Characteristic odour.
pH	<i>No data available.</i>
Boiling point/boiling range	135 °C
Melting point	<i>Not applicable.</i>
Flammability (solid, gas)	Not classified
Explosive properties	Not classified
Oxidising properties	Not classified
Flash point	24 °C
Flammable Limits(LEL)	1 % volume
Flammable Limits(UEL)	7 % volume
Vapour pressure	0.6 kPa

3M 08868 High Quality Anti-Chip Coating, Black

Relative density	1.2 [Ref Std: WATER=1]
Water solubility	Nil
Partition coefficient: n-octanol/water	No data available.
Evaporation rate	No data available.
Vapour density	No data available.
Viscosity	2200 mPa-s [@ 20 °C]
Density	1.2 g/cm ³

9.2. Other information

Volatile organic compounds (VOC)	43.48 %
Percent volatile	43.5 %

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon dioxide.	Not specified.
Carbon monoxide.	Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

3M 08868 High Quality Anti-Chip Coating, Black**Eye contact**

Contact with the eyes during product use is not expected to result in significant irritation.

Skin contact

Moderate skin irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Dermal Defatting: Signs/symptoms may include localised redness, itching, drying and cracking of skin.

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Ingestion

May be harmful if swallowed.

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Target Organ Effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data**Acute Toxicity**

Name	Route	Species	Value	UN GHS Classification
Overall product	Ingestion		No test data available; calculated ATE4593 mg/kg	Category5 (30% unknown)
Limestone			No data available	
Xylene			No data available	
Alkyd resin			No data available	
Ethylbenzene			No data available	
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite			No data available	
Carbon black			No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)			No data available	
2-Butanone oxime			No data available	
Lecithin			No data available	
Synthetic amorphous silica, fumed, crystalline free			No data available	

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value	UN GHS Classification
Overall product		No test data available; calculated to be mild irritant	Category 3

3M 08868 High Quality Anti-Chip Coating, Black

Limestone		No data available	
Xylene		Mild irritant	Category 3
Alkyd resin		No data available	
Ethylbenzene	Rabbit	Mild irritant	Category 3
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		No data available	
Carbon black		No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)		No data available	
2-Butanone oxime		No data available	
Lecithin		No data available	
Synthetic amorphous silica, fumed, crystalline free		No data available	

Serious Eye Damage/Irritation

Name	Species	Value	UN GHS Classification
Overall product		No test data available; calculated to cause no significant irritation	Not classified
Limestone		No data available	
Xylene		Moderate irritant	Category 2B
Alkyd resin		No data available	
Ethylbenzene	Human	Moderate irritant	Category 2B
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		No data available	
Carbon black		No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)		No data available	
2-Butanone oxime		No data available	
Lecithin		No data available	
Synthetic amorphous silica, fumed, crystalline free		No data available	

Skin Sensitisation

Name	Species	Value	UN GHS Classification
Overall product		No test data available.	Not classified based on component data
Limestone		No data available	
Xylene		No data available	
Alkyd resin		No data available	
Ethylbenzene		No data available	
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		No data available	
Carbon black		No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)		No data available	
2-Butanone oxime		Sensitising	Category 1
Lecithin		No data available	
Synthetic amorphous silica, fumed, crystalline free		No data available	

3M 08868 High Quality Anti-Chip Coating, Black**Respiratory Sensitisation**

Name	Species	Value	UN GHS Classification
Overall product		No test data available.	Not classified based on component data
Limestone		No data available	
Xylene		No data available	
Alkyd resin		No data available	
Ethylbenzene		No data available	
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		No data available	
Carbon black		No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)		No data available	
2-Butanone oxime		No data available	
Lecithin		No data available	
Synthetic amorphous silica, fumed, crystalline free		No data available	

Germ Cell Mutagenicity

Name	Route	Value	UN GHS Classification
Overall product		No data available	Overall Germ Cell Mutagenicity classification Not classified
Overall product		No test data available.	
Limestone		No data available	
Xylene		No data available	
Alkyd resin		No data available	
Ethylbenzene		No data available	
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		No data available	
Carbon black		No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)		No data available	
2-Butanone oxime		No data available	
Lecithin		No data available	
Synthetic amorphous silica, fumed, crystalline free		No data available	

Carcinogenicity

Name	Route	Species	Value	UN GHS Classification
Overall product			No test data available.	Category 2 based on component data
Limestone			No data available	
Xylene			No data available	
Alkyd resin			No data available	
Ethylbenzene			No data available	
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite			No data available	

3M 08868 High Quality Anti-Chip Coating, Black

Carbon black			No data available	
Poly(vinyl chloride-co-isobutyl vinyl ether)			No data available	
2-Butanone oxime			No data available	
Lecithin			No data available	
Synthetic amorphous silica, fumed, crystalline free			No data available	

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration	UN GHS Classification
Overall product		No test data available.				Not classified based on component data
Limestone		No data available				
Xylene		No data available				
Alkyd resin		No data available				
Ethylbenzene		No data available				
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		No data available				
Carbon black		No data available				
Poly(vinyl chloride-co-isobutyl vinyl ether)		No data available				
2-Butanone oxime		No data available				
Lecithin		No data available				
Synthetic amorphous silica, fumed, crystalline free		No data available				

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	UN GHS Classification
Overall product			No test data available.				Category 1 based on component data
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness				Category 3
Xylene	Inhalation	respiratory irritation	May cause respiratory irritation				Category 3

3M 08868 High Quality Anti-Chip Coating, Black

Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness				Category 3
Limestone			No data available				
Alkyd resin			No data available				
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	LOAEL >0.43 mg/l		Category 3
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		Irritation Positive		Not classified
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite			No data available				
Carbon black			No data available				
Poly(vinyl chloride-co-isobutyl vinyl ether)			No data available				
2-Butanone oxime			No data available				
Lecithin			No data available				
Synthetic amorphous silica, fumed, crystalline free			No data available				

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration	UN GHS Classification
Overall product			No test data available.				Category 1 based on component data
Limestone			No data available				
Xylene			No data available				

3M 08868 High Quality Anti-Chip Coating, Black

Alkyd resin			No data available				
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks	Not classified
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years	Not classified
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Inhalation	respiratory system	May cause damage to organs though prolonged or repeated exposure				Category 2
Carbon black			No data available				
Poly(vinyl chloride-co-isobutyl vinyl ether)			No data available				
2-Butanone oxime			No data available				
Lecithin			No data available				
Synthetic amorphous silica, fumed, crystalline free			No data available				

Aspiration Hazard

Name	Value	UN GHS Classification
Overall product	No test data available.	Not classified based on component and/or viscosity data
Limestone	Not an aspiration hazard	Not classified
Xylene	Not an aspiration hazard	Not classified
Alkyd resin	Not an aspiration hazard	Not classified
Ethylbenzene	Not an aspiration hazard	Not classified
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	Not an aspiration hazard	Not classified
Carbon black	Not an aspiration hazard	Not classified
Poly(vinyl chloride-co-isobutyl vinyl ether)	Not an aspiration hazard	Not classified
2-Butanone oxime	Not an aspiration hazard	Not classified
Lecithin	Not an aspiration hazard	Not classified
Synthetic amorphous silica, fumed, crystalline free	Not an aspiration hazard	Not classified

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information

on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

No product test data available.
No component test data available.

12.2. Persistence and degradability

No test data available.

12.3 : Bioaccumulative potential

No test data available.

12.4. Mobility in soil

Please contact 3M for more details.

12.5. Results of the PBT and vPvB assessment

No information available at this time, contact 3M for more details

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations

As a disposal alternative, dispose of waste product in a permitted hazardous waste facility. Incinerate in a permitted hazardous waste incinerator.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 01 11* Waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transportation information

3M 08868 High Quality Anti-Chip Coating, Black

DS-2729-9113-6

ADR/RID: UN1139, COATING SOLUTION, LIMITED QUANTITY, 3., III, (--), ADR Classification Code: F1.**IMDG-CODE:** UN1139, COATING SOLUTION, 3, III, LIMITED QUANTITY, EMS: FE,SE.**ICAO/IATA:** UN1139, COATING SOLUTION, 3., III.**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Carcinogenicity**

<u>Ingredient</u>	<u>CAS Nbr</u>	<u>Classification</u>	<u>Regulation</u>
Xylene	1330-20-7	Gr. 3: Not classifiable	International Agency for Research on Cancer
2-Butanone oxime	96-29-7	Carc.Cat.3	Regulation (EC) No 1272/2008, Table 3.2
2-Butanone oxime	96-29-7	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information.

15.2. Chemical Safety Assessment

Not applicable

SECTION 16: Other information**List of relevant H statements**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H351	Suspected of causing cancer.

List of relevant R-phrases

R10	Flammable.
R11	Highly flammable.
R20	Harmful by inhalation.
R21	Harmful in contact with skin.
R38	Irritating to skin.
R40	Limited evidence of a carcinogenic effect.
R41	Risk of serious damage to eyes.
R43	May cause sensitisation by skin contact.

Revision information:

No revision information is available.

DISCLAIMER: The information on this Safety Data Sheet is based on 3M's experience and is correct to the best of 3M's knowledge at the date of publication. 3M does not accept liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at www.3M.com/uk