

# DELTA FORCE PLUS

## HIGHLY CONCENTRATED HEAVY DUTY CLEANER/DEGREASER & TRAFFIC FILM REMOVER

**Incredible Cleaner !:** Removes the complete range of stubborn and tenacious road traffic film and dirt. Dried/baked on flies and insects simply dissolve away !

**Paint & Trim Friendly:** Kind to paintwork, trim and vehicle signwriting. Will not mark or dull surfaces: totally safe cleaning action even with repeated use.

**Wax Effect:** Leaves paintwork clean, bright, reflective and with water beading surface enhancers.

**Super Concentrated:** Gives dramatic savings when pre-diluted before use (see directions).

**Versatile:** Can be used hot or cold, ONE professional product for:

TRAFFIC FILM REMOVAL: State-of-the-art performance.

SUPER DEGREASING: engines, chassis, chains, fork lift trucks, plant hire.

DEWAXING: as a manual Co-polymer Dewaxer.

**Floor Cleaner:** Superb industrial floor cleaner for both painted and tarmac surfaces.

**Environment Safe:** Fully biodegradable to EC standards; contains no solvents, no phosphates, no silicates.

**DIRECTIONS :** Delta Force Plus is a fully concentrated product which must be pre-diluted before use. Normal method of applications is by Low Pressure Spray, Proxima Brush (manual cleaning) or High Pressure Application. See application note before use.

**Low Pressure Pre-spray :** Delta Force Plus should be pre-diluted with 20 to 25 parts of water depending on degree of soiling. 1 litre of concentrate therefore typically makes 25 litres of pre-spray solution.

Delta Force Plus is a Trade Mark of Concept Chemicals & Coatings Ltd

### Low Pressure (Pre-Spray)

TFR Cold Degreasing  
1:25 1:8

### Hot High Pressure

TFR Degreasing  
1:250 1:80

**High Pressure Cleaning :** To gain maximum economy and performance in use pre-dilute the concentrate **prior** to placing in the detergent feed tank/pick up pipe, with between 3 and 7 parts water. 5 litres of concentrate will typically make between 25 and 40 litres of ready to use T.F.R.

**Commercial Truck Cleaning Economy:** Typically dilute 25L at 6:1 to give 175L of solution. This solution is then diluted through the high pressure cleaner at 5% feed rate (5% detergent 95% water). It takes 18L of water to cover the truck (950ml is detergent solution, of which 128ml is original concentrate). Typically 2 minutes are required for application of 18L over truck surface.

**Application Note :** Do not allow material to dry out on any surface or staining mat occur. After use rinse away thoroughly with plenty of cold water. In very hot weather we recommend surfaces being cleaned to be cooled by pre-spraying with cold water before application of cleaning solution.

### Typical Specification :

Composition : A complex blend of non-ionic and cationic surfactants coupled with chelating agents, water and dye.  
Appearance : Clear liquid  
Colour : Cherry red  
S.G. : 1.075  
pH : 13.5  
Odour : Mild  
Shelf Life : Two years minimum in unopened containers at ambient temperature. Protect from freezing.  
Packaging : 5L, 25L, 200L & 1000L containers.