

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

1 Identification of the substance/preparation and of the company/undertaking

For professional use only

· **Product details**

· **Trade name:** *EM307-EM312 1K RapidCoat Primer (Contains Lead)*

· **Application of the substance / the preparation**

Coating compound/ Surface coating/ paint
High Build Primer

· **Manufacturer/Supplier:**

TRADE AUTOMOTIVE SUPPLIES LIMITED
REFINISH HOUSE, GELDERS HALL INDUSTRIAL ESTATE
SHEPSHED, LEICESTERSHIRE, LE12 9NH
TELEPHONE: 01509 651 122
FAX: 01509 651 166

· **Further information obtainable from:** *sales@tradegroup.co.uk*

· **Information in case of emergency:** *sales@tradegroup.co.uk*

2 Hazards identification

· **Hazard description:**



T Toxic
N Dangerous for the environment

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 45 May cause cancer.

R 61 May cause harm to the unborn child.

R 10 Flammable.

R 20/21 Also harmful by inhalation and in contact with skin.

R 33 Danger of cumulative effects.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

1330-20-7	Xylene (mix)
67-63-0	propan-2-ol

3 Composition/information on ingredients

· **Chemical characterization**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7	Xylene (mix) ☒ Xn, ☒ Xi; R 10-20/21-38	25-50%
CAS: 7727-43-7 EINECS: 231-784-4	barium sulphate, natural	2.5-10%
CAS: 7779-90-0 EINECS: 231-944-3	trizinc bis(orthophosphate) ☒ N; R 50/53	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ☒ Xn; R 65	2.5-10%

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

Trade name: EM307-EM312 1K RapidCoat Primer (Contains Lead)

(Contd. of page 1)

CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol ☒ Xi, ☒ F; R 11-36-67	≤ 2.5%
	Lead Chromate ☒ T, ☒ N; R 45-61-62-33-50/53	≤ 2.5%
	Lead Carboxylate ☒ T, ☒ N; R 61-62-20/22-33-50/53	≤ 2.5%
CAS: 64742-82-1 EINECS: 265-185-4	Naphtha (petroleum), hydrodesulfurized heavy ☒ N; R 10-51-66	≤ 2.5%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

· **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

· **Measures for environmental protection:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Measures for cleaning/collecting:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

7 Handling and storage

· **Handling:**

· **Information for safe handling:**

Keep receptacles tightly sealed.

Ensure good ventilation/extraction at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

Trade name: EM307-EM312 1K RapidCoat Primer (Contains Lead)

(Contd. of page 2)

Keep respiratory protective device available.

- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 Xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

7727-43-7 barium sulphate, natural

WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
-----	---

67-63-0 propan-2-ol

WEL	Short-term value: 1250 mg/m ³ , 500 ppm Long-term value: 999 mg/m ³ , 400 ppm
-----	--

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

When spraying the product, use a respiratory protective device that is independent of circulating air.

- **Protection of hands:**

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

Trade name: EM307-EM312 1K RapidCoat Primer (Contains Lead)

(Contd. of page 3)

· Eye protection:


Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	137°C

· Flash point:	25°C
-----------------------	------

· Ignition temperature:	450°C
--------------------------------	-------

· Self-igniting:	Product is not selfigniting.
-------------------------	------------------------------

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
-------------------------------	---

· Explosion limits:

Lower:	1.1 Vol %
Upper:	7.0 Vol %

· Vapour pressure at 20°C:	6.7 hPa
-----------------------------------	---------

· Density:	Not determined.
-------------------	-----------------

· Solubility in / Miscibility with water:	NOT MISCIBLE
--	--------------

· Solvent content:

Organic solvents:	37.6 %
Water:	1.0 %

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided:	No decomposition if used according to specifications.
--	---

· Materials to be avoided:	
-----------------------------------	--

· Dangerous reactions	No dangerous reactions known.
------------------------------	-------------------------------

· Dangerous decomposition products:	No dangerous decomposition products known.
--	--

11 Toxicological information

· Acute toxicity:
· LD/LC50 values relevant for classification:
1330-20-7 Xylene (mix)

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

Trade name: EM307-EM312 1K RapidCoat Primer (Contains Lead)

(Contd. of page 4)

7779-90-0 trizinc bis(orthophosphate)

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

Lead Chromate

Oral	LD50	>10000 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
 The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
 Harmful
 Irritant
 Carcinogenic.

12 Ecological information

- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

13 Disposal considerations

- **Product:**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 30
- **UN-Number:** 1263
- **Packaging group:** III
- **Hazard label** 3
- **Special marking:** Symbol (fish and tree)
- **Description of goods:** 1263 PAINT (not viscous)

(Contd. on page 6)

Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

Trade name: EM307-EM312 1K RapidCoat Primer (Contains Lead)

(Contd. of page 5)

- **Maritime transport IMDG:**
- **Marine pollutant:** No

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
 - **Code letter and hazard designation of product:**
T Toxic
N Dangerous for the environment
 - **Hazard-determining components of labelling:**
Lead Chromate
Xylene (mix)
 - **Risk phrases:**
45 May cause cancer.
61 May cause harm to the unborn child.
10 Flammable.
20/21 Also harmful by inhalation and in contact with skin.
33 Danger of cumulative effects.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 - **Safety phrases:**
53 Avoid exposure - obtain special instructions before use.
9 Keep container in a well-ventilated place.
20 When using do not eat or drink.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
57 Use appropriate container to avoid environmental contamination.
 - **Special labelling of certain preparations:**
Contains cobalt bis(2-ethylhexanoate). May produce an allergic reaction.
 - **National regulations:**
 - **Technical instructions (air):**
- | Class | Share in % |
|-------|------------|
| Water | 1.0 |
| II | 1.1 |
| NK | 37.6 |
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
10 Flammable.
11 Highly flammable.
20/21 Harmful by inhalation and in contact with skin.
20/22 Harmful by inhalation and if swallowed.
33 Danger of cumulative effects.

(Contd. on page 7)



Safety Data Sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2010

Revision: 10.04.2009

Trade name: EM307-EM312 1K RapidCoat Primer (Contains Lead)

(Contd. of page 6)

- 36 *Irritating to eyes.*
- 38 *Irritating to skin.*
- 45 *May cause cancer.*
- 50/53 *Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- 51 *Toxic to aquatic organisms.*
- 61 *May cause harm to the unborn child.*
- 62 *Possible risk of impaired fertility.*
- 65 *Harmful: may cause lung damage if swallowed.*
- 66 *Repeated exposure may cause skin dryness or cracking.*
- 67 *Vapours may cause drowsiness and dizziness.*

· **Department issuing MSDS:** Product safety department: LABORATORY

· **Contact:** Health & Safety Officer

GB