



Safety Data Sheet

1. Identification of the Preparation and of the Company.

Product Name: **EuroWave Basecoat Aluminium Tinters**

Part No. **EW500, EW501, EW502, EW503, EW504, EW505, EW506, EW507, EW508, EW509, EW510, EW511, EW512, EW513, EW514**

Use of the Preparation: Refinishing Paint

Supplier: The Trade Group Ltd.
Refinish House
Gelders Hall Industrial Estate
Shepshed, Leicestershire
LE12 9NH
www.tradegroup.co.uk

Tel: 01509 651122
Fax: 01509 651166
e-mail: sales@tradegroup.co.uk

Emergency Tel. **0800 043 1672**

2. Hazards Identification

This product is not a dangerous preparation according to directive 1999/45/EC.

3. Composite / Information on Ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EC and amendments.
For the hazards of the preparation, see Section 2.

SUBSTANCES % by Wt in the product	SYMBOL and R(*) phrases of the pure substances	CAS number	EINECS / ELINCS
ALUMINIUM POWDER (STABILIZED) 3 - < 5%	F R10,R15		231-072-3
2-BUTOXYETHANOL / ETHYLENE GLYCOL MONOBUTYL ETHER 7 - <10%	Xn R20/21/22, R36/38	111-76-2	203-905-0

(*) See full text of phrases under Section 16



Safety Data Sheet

4. First Aid Measures

General :

In all cases of doubt or when symptoms persist, seek medical attention. Have Safety Data Sheet information available. Never give anything by mouth to an unconscious person.

Inhalation :

Remove to fresh air, keep patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

Eye contact :

Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.

Skin contact :

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognized skin cleaners. Do NOT use solvents or thinners.

Ingestion :

If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

5. Fire-Fighting Measures

This product is not combustible.

Use appropriate extinguishing media according to other materials involved in this fire.

Recommendations :

- Fire will produce dense black smoke. Exposure to decomposition products may cause a Health Hazard. Fire fighters should wear self-contained breathing apparatus.
- Water mist may be used to cool closed containers to prevent pressure build-up and possible auto-ignition and explosion when exposed to extreme heat.
- Do not weld, expose to extreme heat or ignition sources, empty containers which have contained flammable products.
- Do not allow run-off from fire fighting to enter drains or water courses.



Safety Data Sheet

6. Accidental Release Measures

- Exclude sources of ignition and ventilate the area. Avoid breathing vapours by using appropriate respiratory protective equipment. Refer to protective measures listed in sections 7 & 8.
- Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for disposal in accordance with local regulations (see section 13). Do not allow to enter drains or watercourses.
- Clean preferably with a detergent ; avoid use of solvents.
- If the product contaminates lakes, rivers or sewers, inform water authorities in accordance with local regulations.

7. Handling & Storage

7.1 Handling

Manual Handling of Loads: Council Directive 90/269/EEC and the Manual Handling Operations Regulations may apply to the handling of certain paint products.

- Smoking, eating and drinking should be prohibited during handling.
- Keep container tightly closed. Any containers which are open should be carefully resealed.
- Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Packaging materials :

- Recommended : keep preferably in original container.
- Avoid :
 - *Those sensitive to water

- Handle and open containers with care to avoid sudden ejections. Never use pressure to empty : container is not a pressure vessel. Clean or discard contaminated clothing and shoes.
- Wear appropriate respiratory equipment when paint spraying, even outdoors. In all cases when working in a confined area or spraybooth, or where ventilation is unlikely to be sufficient to control particulates and solvent vapour, operators should wear a compressed airfed respirator during the spraying process.

The accumulation of dry overspray, contaminated rags, etc. may result in spontaneous combustion. Good housekeeping standards, the regular maintenance of spray booth filters and the regular and safe removal of waste materials will minimise the risk.

7.2 Storage

Observe label precautions. Store between 5 and 35°C in a dry, clean and well ventilated place, away from sources of heat, ignition, and direct sunlight.

Store in accordance with The Dangerous Substances and Explosive Atmospheres Regulations 2002.



Safety Data Sheet

8. Exposure Controls / Personal Protection

8.1 Engineering measures

Avoid the inhalation of vapour, spray mist and particulates. This should be achieved by the provision of local exhaust ventilation and good general extraction to keep air-borne concentration below the Occupational Exposure Limits (OEL). If these are not sufficient to comply with OEL, suitable respiratory protection must be worn.

8.2 Exposure limits

Substances	----- Workplace Exposure limit (.)-----				Comments
	8-hr limit		15-minute limit		
	ppm	mg/m ³	ppm	mg/m ³	
2-BUTOXYETHANOL/ETHYLENE GLYCOL MONOBUTHYL ETHER	25	-	50	-	Sk
ALUMINIUM POWDER (STABILIZED)	-	4	-	-	RD

(.) : See Guidance Note EH 40, Workplace exposure limits

Carc : Capable of causing cancer

Sk : Can be absorbed through skin

Sen : Capable of causing occupational asthma

RD : Respirable dust

-. : Not estimated

8.3 Personal protection

All Personal Protective Equipment, including Respiratory Protective Equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

Respiratory protection :

Appropriate certified respiratory protective equipment should be selected according to the type of contaminants, following official and manufacturers instructions including proper fitting

The European Group of Vehicle Refinish Manufacturers united in CEPE recommends the use of fresh-air masks as the best personal protection during spraying of any car refinish paint.

Hand protection :

For prolonged or repeated contact, we recommend gloves type : nitrile rubber, neoprene rubber. Barrier creams may help to protect exposed areas of skin. However, they should not be applied once exposure has occurred.

Eye protection :

Use safety glasses to protect against splashes.



Safety Data Sheet

Skin protection :

Personnel should wear protective clothing made of antistatic and fire resistant fibres. All parts of the body should be washed after contact with the product.

Use good hygiene and industrial practices, keeping working clothes clean.

All the above precautions also apply to dry sanding and thermal decomposition, eg welding or flame cutting of the dried product, which will give rise to dust and/or fumes.

Steps must be taken to ensure that persons nearby who may be unconnected with the spraying, sanding or hot-work operations, are not affected.

9. Physical and Chemical Properties

- Physical state at 20°C : Liquid
- Flash point : $\geq 100^{\circ}\text{C}$ Method : ISO 3679
 - The product does not support combustion Method : ISO/TR 9038
- Viscosity : 30 - < 40 secs Method : ISO 2431 (6mm)
- Specific gravity at 20°C : 1.0 g/cm³ Method : ISO 2811
- Vapour density : > air
- Lower explosion limit (vol %) : 1.0 (2-BUTOXYETHANOL/ ETHYLENE GLYCOL MONOBUTYL ETHER)
- Upper explosion limit (vol %) : 10.6 (2-BUTOXYETHANOL/ ETHYLENE GLYCOL MONOBUTYL ETHER)
- Miscibility in water at 20°C : partially miscible
- pH : not applicable
- Vapour pressure at 20°C : 17 mm Hg

10. Stability and Reactivity

Stable under recommended storage and handling conditions (see section 7).

In case of combustion, may produce hazardous decomposition products such as :

- Carbon monoxide

11. Toxicological Information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See Sections 3 and 15 for details.



Safety Data Sheet

In the case of 2-BUTOXYETHANOL / ETHYLENE GLYCOL MONOBUTYL ETHER there is evidence of skin penetration and possible harmful effects in the blood.

12. Ecological information

There is no data available on the preparation itself.
The product should not be allowed to enter drains or water courses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and not classified as dangerous for the environment.

13. Disposal Considerations

The provisions of Council Directive 91/689/EEC and subsequent Amendments and Decisions apply to wastes from the product as supplied.

EWC- Code : 08 01 11

Hazardous Properties : not applicable.

It is recommended that the container is emptied of as much material as possible prior to recycling or disposal of the container.

Store waste in accordance with The Dangerous Substances and Explosive Atmospheres Regulations 2002.

Do not allow into drains or water courses.

Waste and emptied containers must be disposed in accordance with :

- Environment Protection Act
- Control of Pollution Act 1974,
- Special Waste Regulations 1996,

They should be recycled or disposed of through a licenced waste management facility.

Wastes derived from the product may be subject to the classification requirements of the Directive and the Special Waste Regulations.



Safety Data Sheet

14. Transport Information

UN number : None
PROPER SHIPPING NAME : Paint – Non-Regulated Goods
N.O.S. Technical Name : None
Class : None
Subsidiary Class(es): None
Packing group : None.

ADR/RID
TREM CARD: None

IMDG
EMS No.: None
ICAO/IATA
Passenger Air Packing Instruction : None
Passenger Air Max Quantity/Package : None
Cargo Air Packing Instruction : None
Cargo Air Max Quantity/Package : None

15. Regulatory Information

LABEL

According to the Directive (1999/45/EC), relating to the classification packaging and labelling of dangerous substances and preparations, the product is labelled as follows :

- P101 SAFETY DATA SHEET AVAILABLE FOR PROFESSIONAL USER ON REQUEST
- S23+S38 Do not breathe vapour / spray. In case of insufficient ventilation, wear suitable respiratory equipment.
- The provisions of the Health and Safety at Work Act, the Control of Substances Hazardous to Health Regulations and The Dangerous Substances and Explosive Atmospheres Regulations apply to the use of this product at work.

16. Other Information

Full text of R phrases with N° appearing in Section 3:

- R10 FLAMMABLE
- R15 Contact with water liberates extremely flammable gases.
- R20/21/22 Harmful by inhalation and in contact with skin and if swallowed.
- R36/38 Irritating to eyes and skin.



Safety Data Sheet

The information contained in this data sheet is based on present scientific and technical knowledge. AS OF : 29-6-2007

The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by The Trade Group, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

The information contained in this Safety Data Sheet is provided in accordance with the requirements of Regulation (EC) No 1907/2006 and the Chemicals (Hazard Information and Packaging) Regulations.

END OF SAFETY DATA SHEET