



## SAFETY DATA SHEET

### 800/801 Fusor Match Urethane Sealer Adhesive

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

PRODUCT NAME 800/801 Fusor Match Urethane Sealer Adhesive  
 PRODUCT NO. 76070R  
 SUPPLIER Lord Corporation (Europe) Ltd  
 Chemical Products Division  
 Stretford Motorway Estate, Barton Dock  
 Road  
 Stretford, Manchester. M32 0ZH. United  
 Kingdom  
 +44 (0)161 865 8048  
 +44 (0)161 865 0096

#### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
HYDROCARBON SOLVENT	265-192-2	64742-89-8	1-5%	Carc 1;R45. Xn;R65.
POLYISOCYANATE OF MDI		26447-40-5	< 1%	Xn;R20. Xi;R36/37/38. R42.
XYLENE	215-535-7	1330-20-7	1-5%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

#### 3 HAZARDS IDENTIFICATION

May cause cancer.

CLASSIFICATION Carc 2;R45.

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Remove affected person from source of contamination. Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

##### INHALATION

Move the exposed person to fresh air at once. Get medical attention. Provide rest, warmth and fresh air. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

##### INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Get medical attention immediately! Provide rest, warmth and fresh air.

##### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

##### EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

##### EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

## 800/801 Fusor Match Urethane Sealer Adhesive

### SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

### UNUSUAL FIRE & EXPLOSION HAZARDS

Risk of explosion in closed containers if pressure rises rapidly.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers. Do not contaminate water sources or sewer.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Persons susceptible for allergic reactions should not handle this product.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
XYLENE	OES	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)

### INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation. All handling to take place in well-ventilated area.

### RESPIRATORY EQUIPMENT

Wear suitable respiratory protection.

### HAND PROTECTION

Use protective gloves. SPECIFIC RECOMMENDATIONS. Neoprene. Nitrile.

### EYE PROTECTION

Wear approved safety goggles. Use safety goggles and face shield in case of splash risk.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste
COLOUR	Buff
ODOUR	Mild (or faint).
SOLUBILITY	Insoluble in water

REVISION DATE: 02/11/04

## 800/801 Fusor Match Urethane Sealer Adhesive

RELATIVE DENSITY 1.20 - 1.25 @ 20 °c VOLATILE BY VOL. (%) 5.9  
FLASH POINT (°C) 56 Sh CC (Setaflash closed cup).

### 10 STABILITY AND REACTIVITY

#### STABILITY

Stable under normal temperature conditions.

#### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.

#### MATERIALS TO AVOID

Amines. Strong acids. Strong alkalies. Strong oxidising substances.

#### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrogen cyanide (HCN). Oxides of: Nitrogen.

### 11 TOXICOLOGICAL INFORMATION

#### GENERAL INFORMATION

Known or suspected carcinogen for humans. Preparation contains small volumes of isocyanate which may cause allergic reaction and irritation of respiratory system.

#### INHALATION

May cause irritation to the respiratory system. May cause sensitisation by inhalation.

#### INGESTION

Harmful if swallowed.

#### SKIN CONTACT

May cause skin irritation/eczema May cause sensitisation by skin contact.

#### EYE CONTACT

Irritating to eyes.

#### HEALTH WARNINGS

Known or suspected carcinogen for humans. Prolonged exposure to the preparation may cause serious health effects.

#### ROUTE OF ENTRY

Inhalation. Skin and/or eye contact. Ingestion.

#### TARGET ORGANS

Skin. Eyes. Respiratory system, lungs.

### 12 ECOLOGICAL INFORMATION

#### ECOTOXICITY

No data on possible environmental effects have been found.

### 13 DISPOSAL CONSIDERATIONS

#### GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

#### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION



UK ROAD CLASS

3

REVISION DATE: 02/11/04

## 800/801 Fusor Match Urethane Sealer Adhesive

PROPER SHIPPING NAME	ADHESIVES		
UN NO. ROAD	1133	UK ROAD PACK GR.	III
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	III	HAZARD No. (ADR)	30
ADR LABEL NO.	3	HAZCHEM CODE	3Y
CEVIC TEC(R) NO.	30GF1-III,30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	III	UN NO. SEA	1133
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	III	EMS	F-E, S-D
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1133	ICAO CLASS	3
AIR PACK GR.	III		

### 15 REGULATORY INFORMATION

#### LABELLING



Toxic

#### CONTAINS

HYDROCARBON SOLVENT

#### RISK PHRASES

R45 May cause cancer.

#### SAFETY PHRASES

P4 Contains isocyanates. See information supplied by the manufacturer.  
P11 Restricted to professional users.  
P14 Contains POLYISOCYANATE OF MDI. May produce an allergic reaction.  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
S45 In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).  
S53 Avoid exposure - obtain special instructions before use.  
S60 This material and its container must be disposed of as hazardous waste.

#### EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EEC.

#### STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

#### APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### GUIDANCE NOTES

Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

### 16 OTHER INFORMATION

#### INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

REVISION DATE 02/11/04

REV. NO./REPL. SDS GENERATED 03-11/04/03

SDS NO. LC35-FUSOR 800/801 -04-02/11/04

## 800/801 Fusor Match Urethane Sealer Adhesive

### RISK PHRASES IN FULL

R10	Flammable.
R20	Harmful by inhalation.
R20/21	Harmful by inhalation and in contact with skin.
R36/37/38	Irritating to eyes, respiratory system and skin.
R38	Irritating to skin.
R42	May cause sensitisation by inhalation.
R45	May cause cancer.
R65	Harmful: may cause lung damage if swallowed.

### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.