



SAFETY DATA SHEET SIMONIZ AEROSOL PRIMERS

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	SIMONIZ AEROSOL PRIMERS		
PRODUCT NO.	SIMP11, SIMP11C		
SUPPLIER	Holt Lloyd International Ltd Oakhurst Drive, Lawnhurst Trading Estate Cheadle Heath, Stockport, SK3 0RZ- England +44 (0)161 491 7391 FAX +44 (0)161 491 7399 A Honeywell Consumer Products Group Company www.holtsauto.com	MANUFACTURER	Holt Lloyd International Ltd Oakhurst Drive, Lawnhurst Trading Estate Cheadle Heath, Stockport, SK3 0RZ- England +44 (0)161 491 7391 FAX +44 (0)161 491 7399 A Honeywell Consumer Products Group Company www.holtsauto.com
EMERGENCY TELEPHONE	FR - INRS Tél :+33 (0)1.45.42.59.59 24hrs B - Antigifcentrum Tél: +32.70.245.245 24hrs NL - Rijksinstituut voor Volksgezondheid en Milieuhygiëne: tel. +31 (0)30 274 91 11 24hrs UK - 00 44 (0) 161 491 7391office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167		

2 HAZARDS IDENTIFICATION

Extremely flammable. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin. Possible risk of harm to the unborn child.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

CLASSIFICATION Xn;R48/20. Rep 3;R63. Xi;R36/38. F+;R12. R67.

PHYSICAL AND CHEMICAL HAZARDS

The product is extremely flammable, and explosive vapour/air mixtures may be formed even at normal room temperatures. Closed containers can burst violently when heated, due to excess pressure build-up.

HUMAN HEALTH

In high concentrations, vapours may be irritating to the respiratory system.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
ACETONE	200-662-2	67-64-1	30-60%	F;R11 Xi;R36 R66 R67
TOLUENE	203-625-9	108-88-3	10-30%	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67
BUTANE	203-448-7	106-97-8	10-30%	F+;R12
ISOBUTYL ACETATE	203-745-1	110-19-0	5-10%	F;R11 R66
ISOBUTANE	200-857-2	75-28-5	5-10%	F+;R12
XYLENE	215-535-7	1330-20-7	5-10%	R10 Xn;R20/21 Xi;R38
XYLENE-ortho	202-422-2	95-47-6	1-5%	R10 Xn;R20/21 Xi;R38
PROPAN-2-OL	200-661-7	67-63-0	1-5%	F;R11 Xi;R36 R67
ISO-BUTANOL	201-148-0	78-83-1	1-5%	R10 Xi;R37/38,R41 R67
ALKYLAMMONIUM SALT			< 1%	Xi;R36/37/38. N;R51/53.

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

NOTE! Keep affected person away from heat, sparks and flames! Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

SIMONIZ AEROSOL PRIMERS

INGESTION

Not relevant.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

EYE CONTACT

Spray in the eyes: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

UNUSUAL FIRE & EXPLOSION HAZARDS

Risk of explosion if heated. If heated, volume and pressure increases strongly, resulting in explosion of container.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. When dealing with a spillage, please consult the section relating to suitable protective measures.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	
BUTANE	WEL	600 ppm	1450 mg/m3	750 ppm	1810 mg/m3	
ISOBUTANE	OES	800 ppm		800 ppm		
ISO-BUTANOL	WEL	50 ppm	154 mg/m3	75 ppm	231 mg/m3	
ISOBUTYL ACETATE	WEL	150 ppm	724 mg/m3	187 ppm	903 mg/m3	
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	150 ppm(Sk)	574 mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

INGREDIENT COMMENTS

WEL = Workplace Exposure Limits

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level.

SIMONIZ AEROSOL PRIMERS**ENGINEERING MEASURES**

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves. Rubber gloves are recommended. EN374

EYE PROTECTION

Use eye protection. Goggles/face shield are recommended.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Aerosol
COLOUR	Grey
ODOUR	Solvent.
SOLUBILITY	Insoluble in water Soluble in Acetone Organic solvents
RELATIVE DENSITY	0.911

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

11 TOXICOLOGICAL INFORMATION**INHALATION**

Harmful: danger of serious damage to health by prolonged exposure through inhalation. When working extensively on big surfaces in small and badly ventilated rooms, vapours may develop in concentrations which may cause headache and irritation of the eyes and the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea.

INGESTION

No harmful effects expected in amounts likely to be ingested by accident.

SKIN CONTACT

Repeated exposure may cause skin dryness or cracking. Prolonged or repeated exposure may cause severe irritation. Irritating to skin.

EYE CONTACT

Irritating to eyes. Repeated exposure may cause chronic eye irritation.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

The product is not expected to be hazardous to the environment. However, The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

13 DISPOSAL CONSIDERATIONS**DISPOSAL METHODS**

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL	Limited Quantities
PROPER SHIPPING NAME	AEROSOLS

SIMONIZ AEROSOL PRIMERS

UN NO. ROAD	1950	ADR CLASS NO.	2
ADR PACK GROUP	5F	RID CLASS NO.	2
UN NO. SEA	1950	IMDG CLASS	2.1
EMS	F-D, S-U	MARINE POLLUTANT	No.
UN NO. AIR	1950	AIR CLASS	2.1

15 REGULATORY INFORMATION

LABELLING



Harmful



Extremely Flammable

CONTAINS

TOLUENE

RISK PHRASES

R12	Extremely flammable.
R36/38	Irritating to eyes and skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R63	Possible risk of harm to the unborn child.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S2	Keep out of the reach of children
S13	Keep away from food, drink and animal feeding stuffs.
S16	Keep away from sources of ignition - No smoking.
S23	Do not breathe vapour/spray.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37	Wear suitable protective clothing and gloves.
S51	Use only in well-ventilated areas.
A1	Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2	Do not spray on a naked flame or any incandescent material.

UK REGULATORY REFERENCES

Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.

ENVIRONMENTAL LISTING

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

NATIONAL REGULATIONS

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. No. 1689. Workplace Exposure Limits 2005 (EH40) The Aerosol Dispensers (EEC Requirements)(Amendment) Regulations 1996 (SI 1996 No 2421). Control of Substances Hazardous to Health Regulations 2002 (as amended) The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2007 (CDG 2007)

16 OTHER INFORMATION

GENERAL INFORMATION

EU limit value for this product (Category B/e): 840 g/l. No product listed on this Safety Data Sheet has a maximum VOC content greater than: 720 g/l

SIMONIZ AEROSOL PRIMERS

REVISION COMMENTS

Change of reference number.

ISSUED BY

Technical Department

REVISION DATE 02/04/2009

REV. NO./REPL. SDS GENERATED 1

SDS NO. 10935

SAFETY DATA SHEET STATUS

Approved.

DATE 17-05-05

RISK PHRASES IN FULL

R12	Extremely flammable.
R10	Flammable.
R20/21	Harmful by inhalation and in contact with skin.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R65	Harmful: may cause lung damage if swallowed.
R11	Highly flammable.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36	Irritating to eyes.
R37/38	Irritating to respiratory system and skin.
R38	Irritating to skin.
R63	Possible risk of harm to the unborn child.
R66	Repeated exposure may cause skin dryness or cracking.
R41	Risk of serious damage to eyes.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.