



This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet.

SAFETY DATA SHEET

1. Identification of the substance/preparation and company/undertaking

Product name and/or code : Chassis Black

Manufacturer : Akzo Nobel Car Refinishes bv
Rijksstraatweg 31
2171 AJ Sassenheim
The Netherlands
Phone: +31 (0)71 308 6944

Emergency telephone number of the company : + 31 (0)71 308 6944

2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS no.	%	EC number	Classification
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	25 - 50	265-185-4	R10 Xn; R65 N; R51/53
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	2.5 - 10	265-185-4	R10 Xn; R65 R66, R67 N; R51/53
Xylene	1330-20-7	1 - 2.5	215-535-7	R10 Xn; R20/21 Xi; R38
hexanoic acid, 2-ethyl-, zirconium salt	22464-99-9	1 - 2.5	245-018-1	Xi; R38
Naphtha (petroleum), hydrotreated heavy	64742-48-9	1 - 2.5	265-150-3	Xn; R65 R66
hexanoic acid, 2-ethyl-, cobalt salt	13586-82-8	0 - 1	237-015-9	Xn; R22 Xi; R38 R43
2-butanone oxime	96-29-7	0 - 1	202-496-6	Carc. Cat. 3; R40 Xn; R21 Xi; R41 R43
Naphtha (petroleum), hydrotreated heavy	64742-48-9	0 - 1	265-150-3	R10 Xn; R65 R66, R67
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : R10
N; R51/53

4. First-aid measures

First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious place in recovery position and seek medical advice.

- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO₂, powders, water spray.
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways

6. Accidental release measures

- Personal precautions** : Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- Treatments such as sanding, welding, burning off, etc. of paint films may generate hazardous dust and/or fumes. Work in well ventilated areas. Use suitable personal (respiratory) protective equipment, as necessary.
- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.
- Keep away from: oxidising agents, strong alkalis, strong acids.
No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
Do not empty into drains..

8. Exposure controls/personal protection

Engineering measures : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
Naphtha (petroleum), hydrodesulfurized heavy	80/1107/EEC (Europe). Notes: Suppliers information TWA: 100 ppm 8 hour/hours. TWA: 500 mg/m ³ 8 hour/hours.
Xylene	EH40-OES (United Kingdom (UK), 5/2003). Skin STEL: 441 mg/m ³ 15 minute/minutes. Form: All forms STEL: 100 ppm 15 minute/minutes. Form: All forms TWA: 220 mg/m ³ 8 hour/hours. Form: All forms TWA: 50 ppm 8 hour/hours. Form: All forms
hexanoic acid, 2-ethyl-, zirconium salt	EH40-OES (United Kingdom (UK), 5/2003). STEL: 10 mg/m ³ 15 minute/minutes. Form: All forms TWA: 5 mg/m ³ 8 hour/hours. Form: All forms
Naphtha (petroleum), hydrotreated heavy	: 1200 mg/m ³ : 197 ppm
hexanoic acid, 2-ethyl-, cobalt salt	EH40-MEL (United Kingdom (UK), 5/2003). TWA: 0.1 mg/m ³ 8 hour/hours. Form: All forms

Personal protective equipment

- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Skin and body** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- Hands** : For prolonged or repeated handling, use gloves: neoprene or nitrile.
- Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.
- Eyes** : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: 39°C (102.2°F).
- Viscosity** : Kinematic: 776.699 cSt
- Relative density** : 1.03 (Water = 1)
- Vapour density** : The highest known value is 4.5 (Air = 1) (Naphtha (petroleum), hydrodesulfurized heavy).
Weighted average: 4.37 (Air = 1)
- Lower explosion limit** : The greatest known range is Lower: 1% Upper: 7.5% (xylene)
- Solubility** : Partially soluble in cold water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains (hexanoic acid, 2-ethyl-, cobalt salt, 2-butanone oxime). May produce an allergic reaction.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See sections 2 and 15 for details.

Ecotoxicity data

<u>Ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Xylene	Oncorhynchus mykiss (LC50)	96 hour/hours	3.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	8.2 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	8.6 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	12 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	13.3 mg/l
	Pimephales promelas (LC50)	96 hour/hours	13.4 mg/l
2-butanone oxime	Pimephales promelas (LC50)	96 hour/hours	843 mg/l

Ecological information

Persistence/degradability

<u>Ingredient name</u>	<u>Aquatic half-life</u>	<u>Photolysis</u>	<u>Biodegradability</u>
Not readily	-	-	Not readily

13. Disposal considerations

Do not allow to enter drains or watercourses.
Dispose of according to all federal, state and local applicable regulations.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

14. Transport information

Land - road/railway

UN number	: UN1263
Transport document name	: PAINT
Special provision 640	: E
ADR/RID Class	: 3
Packing group	: III
ADR/RID Label	: Exempted according to 2.2.3.1.5 (Viscous substance exemption)



Sea

UN number	: UN1263
Proper shipping name	: PAINT
Marine pollutant substances	: Naphtha (petroleum), hydrodesulfurized heavy, Naphtha (petroleum), hydrodesulfurized heavy
IMDG Class	: 3
Packing group	: III
IMDG Label	: Exempted according to 2.2.3.1.5 (Viscous substance exemption)



Marine pollutant : Yes.

Air

UN number	: UN1263
Proper shipping name	: PAINT
ICAO/IATA Classification	: 3
Packing group	: III

ICAO/IATA label

:

Inland waterways

UN number : UN1263

Proper shipping name : PAINT

ADNR Classification : 3

Packing group : III

ADNR Label :

**15. Regulatory information**EU regulations

: The product is labelled as follows, in accordance with local regulations:

Hazard symbol/symbols

:



Dangerous for the environment.

Risk phrases

: R10- Flammable.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases

: S23- Do not breathe vapor/spray.

Other EU regulations

Additional warning phrases

: Contains (hexanoic acid, 2-ethyl-, cobalt salt, 2-butanone oxime). May produce an allergic reaction.

VOC content (industrial use)

: Contains 11.5032 wt% VOC. Contains 0 wt% carbon as VOC. This product contains VOC/VOC's. You may be subject to environmental control legislation under Integrated Pollution Control (IPC) or Integrated Pollution Prevention and Control (IPPC) Regulations. Contact your local Environmental Agency Office if in doubt.

16. Other information

CEPE Classification

: 1

Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)

: R10- Flammable.
R40- Limited evidence of a carcinogenic effect.
R20/21- Harmful by inhalation and in contact with skin.
R21- Harmful in contact with skin.
R22- Harmful if swallowed.
R65- Harmful: may cause lung damage if swallowed.
R38- Irritating to skin.
R41- Risk of serious damage to eyes.
R43- May cause sensitisation by skin contact.
R66- Repeated exposure may cause skin dryness or cracking.
R67- Vapours may cause drowsiness and dizziness.
R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.**The information in this Safety Data Sheet is required according to EU Directive 91/155/EEC and its amendments.**

Date of issue

: 7/21/2005.

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.