

AKZO NOBEL

This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet.

sikkens

SAFETY DATA SHEET

1. Identification of the substance/preparation and company/undertaking

Product name and/or code : **Autocoat BT 800 Washprimer Beige 8004-005**

Manufacturer : Akzo Nobel Car Refinishes bv
Rijksstraatweg 31
2171 AJ Sassenheim
The Netherlands
Phone: +31 (0)71 308 6944
<http://www.sikkenscr.com>

Emergency telephone number of the company : + 31 (0)71 308 6944

2. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS no.	%	EC number	Classification
Ethanol	64-17-5	10 - 25	200-578-6	F; R11
Xylene	1330-20-7	10 - 25	215-535-7	R10 Xn; R20/21 Xi; R38
4-Methylpentan-2-one	108-10-1	10 - 25	203-550-1	F; R11 Xn; R20 Xi; R36/37 R66
n-butyl acetate	123-86-4	2.5 - 10	204-658-1	R10 R66, R67
Butan-1-ol	71-36-3	2.5 - 10	200-751-6	R10 Xn; R22 Xi; R37/38, R41 R67
2-Methylpropan-1-ol	78-83-1	2.5 - 10	201-148-0	R10 Xi; R37/38, R41 R67
phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]	25036-25-3	2.5 - 10		Xi; R36/38 R43
2-Methoxy-1-methylethyl acetate	108-65-6	2.5 - 10	203-603-9	R10 Xi; R36
zinc chromates	11103-86-9	2.5 - 10	234-329-8	Carc. Cat. 1; R45 Xn; R22 R43 N; R50/53
Ethyl acetate	141-78-6	1 - 2.5	205-500-4	F; R11 Xi; R36 R66, R67
Ethylbenzene	100-41-4	1 - 2.5	202-849-4	F; R11 Xn; R20
phenol	108-95-2	0 - 1	203-632-7	Muta. Cat. 3; R68 T; R23/24/25 Xn; R48/20/21/22 C; R34
See section 16 for the full text of the R-phrases declared above				
See section 16 for the full text of the R-phrases declared above				

Occupational exposure limits, if available, are listed in section 8.

3. Hazards identification

The preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification	: F; R11 Carc. Cat. 1; R45 Xn; R20 Xi; R37/38, R41 R43 N; R51/53
Physical/chemical hazards	: Highly flammable.
Human health hazards	: Harmful by inhalation. Irritating to respiratory system and skin. Risk of serious damage to eyes. May cause sensitisation by skin contact. May cause cancer.
Environmental hazards	: Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

4. First-aid measures

First-aid measures

General	: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
Ingestion	: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

5. Fire-fighting measures

Extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray. Not to be used : water jet.
Recommendations	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

6. Accidental release measures

Personal precautions	: Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
Spill	: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

Note: see section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

Handling	: Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. To dissipate static electricity during transfer, earth drum and connect to receiving container with bonding strap. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
-----------------	---

Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.

Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.

Put on appropriate personal protective equipment (see section 8).

Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.

Comply with the health and safety at work laws.

When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

Storage

- : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from: oxidising agents, strong alkalis, strong acids.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Do not empty into drains..

8. Exposure controls/personal protection

Engineering measures

- : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
Ethanol	EH40-WEL (United Kingdom (UK), 1/2005). TWA: 1920 mg/m ³ 8 hour/hours. Form: All forms TWA: 1000 ppm 8 hour/hours. Form: All forms
Xylene	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 441 mg/m ³ 15 minute/minutes. Form: All forms STEL: 100 ppm 15 minute/minutes. Form: All forms TWA: 220 mg/m ³ 8 hour/hours. Form: All forms TWA: 50 ppm 8 hour/hours. Form: All forms
4-Methylpentan-2-one	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 416 mg/m ³ 15 minute/minutes. Form: All forms STEL: 100 ppm 15 minute/minutes. Form: All forms TWA: 208 mg/m ³ 8 hour/hours. Form: All forms TWA: 50 ppm 8 hour/hours. Form: All forms
n-butyl acetate	EH40-WEL (United Kingdom (UK), 1/2005). STEL: 966 mg/m ³ 15 minute/minutes. Form: All forms STEL: 200 ppm 15 minute/minutes. Form: All forms TWA: 724 mg/m ³ 8 hour/hours. Form: All forms TWA: 150 ppm 8 hour/hours. Form: All forms
Butan-1-ol	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 154 mg/m ³ 15 minute/minutes. Form: All forms STEL: 50 ppm 15 minute/minutes. Form: All forms
2-Methylpropan-1-ol	EH40-WEL (United Kingdom (UK), 1/2005). STEL: 231 mg/m ³ 15 minute/minutes. Form: All forms STEL: 75 ppm 15 minute/minutes. Form: All forms TWA: 154 mg/m ³ 8 hour/hours. Form: All forms TWA: 50 ppm 8 hour/hours. Form: All forms
2-Methoxy-1-methylethyl acetate	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 548 mg/m ³ 15 minute/minutes. Form: All forms STEL: 100 ppm 15 minute/minutes. Form: All forms TWA: 274 mg/m ³ 8 hour/hours. Form: All forms TWA: 50 ppm 8 hour/hours. Form: All forms
zinc chromates	EH40-WEL (United Kingdom (UK), 1/2005). Notes: As Cr TWA: 0.05 mg/m ³ 8 hour/hours. Form: All forms
Ethyl acetate	EH40-WEL (United Kingdom (UK), 1/2005). STEL: 400 ppm 15 minute/minutes. Form: All forms TWA: 200 ppm 8 hour/hours. Form: All forms
Ethylbenzene	EH40-WEL (United Kingdom (UK), 1/2005). Skin STEL: 552 mg/m ³ 15 minute/minutes. Form: All forms STEL: 125 ppm 15 minute/minutes. Form: All forms TWA: 441 mg/m ³ 8 hour/hours. Form: All forms

phenol

TWA: 100 ppm 8 hour/hours. Form: All forms
EH40-WEL (United Kingdom (UK), 1/2005). Skin
 TWA: 2 ppm 8 hour/hours. Form: All forms

Personal protective equipment

Respiratory system : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Skin and body : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.

Hands

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Eyes : Use safety eyewear designed to protect against splash of liquids.

Environmental exposure controls

Do not allow to enter drains or watercourses.

9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: 8°C (46.4°F).

pH : Basic.

Viscosity : Kinematic: 976.744 cSt

Relative density : 1.075 (Water = 1)

Vapour density : The highest known value is 4.6 (Air = 1) (2-methoxy-1-methylethyl acetate). Weighted average: 3.07 (Air = 1)

Lower explosion limit : The greatest known range is Lower: 4.3% Upper: 19% (ethanol)

Solubility : Partially soluble in cold water.

10. Stability and reactivity

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

11. Toxicological information

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 2 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Solvents may cause some of the above effects by absorption through the skin. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains (phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane], zinc chromates). May produce an allergic reaction.

12. Ecological information

There is no data available on the preparation itself.
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is classified for eco-toxicological properties accordingly. See Sections 2 and 15 for details.

Ecotoxicity data

<u>Product/ingredient name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
Ethanol	Daphnia magna (EC50)	48 hour/hours	2 mg/l
	Daphnia magna (EC50)	48 hour/hours	9.3 mg/l
	Daphnia magna (EC50)	48 hour/hours	>100 mg/l
	Daphnia magna (LC50)	96 hour/hours	>100 mg/l
	Pimephales promelas (LC50)	96 hour/hours	>1000 mg/l
Xylene	Oncorhynchus mykiss (LC50)	96 hour/hours	13000 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	3.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	8.2 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	8.6 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	12 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	13.3 mg/l
	Pimephales promelas (LC50)	96 hour/hours	13.4 mg/l
4-Methylpentan-2-one	Scenedesmus subspicatus (EC50)	48 hour/hours	980 mg/l
	Scenedesmus subspicatus (EC50)	48 hour/hours	2000 mg/l
	Pimephales promelas (LC50)	96 hour/hours	505 mg/l
	Pimephales promelas (LC50)	96 hour/hours	537 mg/l
	Pimephales promelas (LC50)	96 hour/hours	540 mg/l
n-butyl acetate	Pimephales promelas (EC50)	48 hour/hours	19 mg/l
	Pimephales promelas (LC50)	96 hour/hours	18 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	100 mg/l
Butan-1-ol	Daphnia magna (EC50)	48 hour/hours	1983 mg/l
	Lepomis macrochirus (LC50)	96 hour/hours	100 mg/l
	Pimephales promelas (LC50)	96 hour/hours	1730 mg/l
	Pimephales promelas (LC50)	96 hour/hours	1910 mg/l
	Pimephales promelas (LC50)	96 hour/hours	1940 mg/l
2-Methylpropan-1-ol	Scenedesmus subspicatus (EC50)	48 hour/hours	230 mg/l
	Daphnia pulex (EC50)	48 hour/hours	1100 mg/l
	Scenedesmus subspicatus (EC50)	48 hour/hours	1250 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	1330 mg/l
	Pimephales promelas (LC50)	96 hour/hours	1430 mg/l
	Pimephales promelas (LC50)	96 hour/hours	1510 mg/l
	Pimephales promelas (EC50)	48 hour/hours	260 mg/l
Ethyl acetate	Scenedesmus subspicatus (EC50)	48 hour/hours	3300 mg/l
	Scenedesmus subspicatus (EC50)	48 hour/hours	5600 mg/l
	Pimephales promelas (LC50)	96 hour/hours	230 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	425.3 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	484 mg/l
	Daphnia magna (EC50)	48 hour/hours	2.93 mg/l
	Daphnia magna (EC50)	48 hour/hours	2.97 mg/l
Ethylbenzene	Selenastrum capricornutum (EC50)	48 hour/hours	7.2 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	4.2 mg/l
	Pimephales promelas (LC50)	96 hour/hours	9.09 mg/l
	Poecilia reticulata (LC50)	96 hour/hours	9.6 mg/l
	Daphnia magna (EC50)	48 hour/hours	4.2 mg/l
Phenol	Daphnia magna (EC50)	48 hour/hours	5.55 mg/l
	Daphnia magna (EC50)	48 hour/hours	6.6 mg/l
	Cyprinus carpio (LC50)	96 hour/hours	0.00175 mg/l
	Daphnia magna (LC50)	96 hour/hours	4 mg/l
	Oncorhynchus mykiss (LC50)	96 hour/hours	5.02 mg/l

13. Disposal considerations

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.

14. Transport information

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Land - road/railway

UN number : UN1263

Transport document name : PAINT

Special provision 640 : H

ADR/RID Class : 3

Packing group : III

ADR/RID Label :



Sea

UN number : UN1263

Proper shipping name : PAINT

Special provisions : Not available.

IMDG Class : 3

Packing group : III

IMDG Label :



Marine pollutant : No.

Emergency schedules (EmS) : F-E, S-E

Air

UN number : UN1263

Proper shipping name : PAINT

Special provisions : Not available.

ICAO/IATA Classification : 3

Packing group : III

The "viscosity exemption" provisions do not apply to air transport.

ICAO/IATA label :



Inland waterways

UN number : UN1263

Proper shipping name : PAINT


ADNR Classification : 3

Packing group : III

ADNR Label :



15. Regulatory information

EU regulations	: The product is classified and labelled for supply in accordance with the Directive 1999/45/EC as follows:
Hazard symbol/symbols	: 
Risk phrases	: Highly flammable, Toxic, Dangerous for the environment. R11- Highly flammable. R45- May cause cancer. R20- Harmful by inhalation. R37/38- Irritating to respiratory system and skin. R41- Risk of serious damage to eyes. R43- May cause sensitisation by skin contact. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases	: S53- Avoid exposure - obtain special instructions before use. S23- Do not breathe vapor/spray. S26- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. S36/37/39- Wear suitable protective clothing, gloves and eye/face protection. S45- In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Contains	: phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane] zinc chromates
Restrictions on the Marketing and Use Directive	: Restricted to professional users.
Industrial use	: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.
VOC content (industrial use)	: Contains 52.869 wt% VOC. Contains 0 wt% carbon as VOC. This product contains VOC/VOC's. You may be subject to environmental control legislation under Integrated Pollution Control (IPC) or Integrated Pollution Prevention and Control (IPPC) Regulations. Contact your local Environmental Agency Office if in doubt.

16. Other information

CEPE Classification	: 1
Full text of R-phrases referred to in sections 2 and 3 - United Kingdom (UK)	: R11- Highly flammable. R10- Flammable. R45- May cause cancer. R68- Possible risk of irreversible effects. R23/24/25- Toxic by inhalation, in contact with skin and if swallowed. R20- Harmful by inhalation. R20/21- Harmful by inhalation and in contact with skin. R22- Harmful if swallowed. R48/20/21/22- Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. R34- Causes burns. R36- Irritating to eyes. R36/37- Irritating to eyes and respiratory system. R36/38- Irritating to eyes and skin. R37/38- Irritating to respiratory system and skin. R38- Irritating to skin. R41- Risk of serious damage to eyes. R43- May cause sensitisation by skin contact. R66- Repeated exposure may cause skin dryness or cracking. R67- Vapours may cause drowsiness and dizziness. R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53- Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

Date of issue : 11/4/2006.

Date of issue : 04 November 2006

Page: 7/8

Version number : 3

Notice to reader

The information in this SDS is based on the present state of our knowledge and on current laws. The product is not to be used for purposes other than those specified under section 1 without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. The information in this SDS is meant to be a description of the safety requirements for our product. It is not to be considered a guarantee of the product's properties.

Version 3**Page: 8/8**