



This product is for the professional painting of vehicles only after reference to the manufacturer's data sheet.

## SAFETY DATA SHEET

### 1. Identification of the substance/preparation and company/undertaking

**Product name and/or code** : Autocoat BT WB 551 Basecoat Activator (solids)

**Manufacturer** : Akzo Nobel Car Refinishes bv  
Rijksstraatweg 31  
2171 AJ Sassenheim  
The Netherlands  
Phone: +31 (0)71 308 6944  
<http://www.sikkenscr.com>

### 2. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

**Classification** : Not classified.

**Additional warning phrases** : Safety data sheet available for professional user on request.

### 3. Composition/information on ingredients

Substances presenting a health or environmental hazard within the meaning of the Dangerous Substances Directive 67/548/EEC.

Chemical name*	CAS no.	%	EC number	Classification
dipropylene glycol methyl ether propan-2-ol	34590-94-8 67-63-0	2.5 - 10 2.5 - 10	252-104-2	Not classified. [2] F; R11 [1] [2] Xi; R36 R67
2-butoxyethanol	111-76-2	2.5 - 10	203-905-0	Xn; R20/21/22 [1] [2] Xi; R36/38
See section 16 for the full text of the R-phrases declared above				

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in section 8.

### 4. First-aid measures

#### First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.
- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

## 5. Fire-fighting measures

- Extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

## 6. Accidental release measures

- Personal precautions** : Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.

**Note: see section 8 for personal protective equipment and section 13 for waste disposal.**

## 7. Handling and storage

- Handling** : Due to the organic solvents content of the preparation:
- Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- Storage** : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.
- Keep away from: oxidising agents, strong alkalis, strong acids.  
No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.  
Do not empty into drains.

## 8. Exposure controls/personal protection

- Engineering measures** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

<u>Ingredient name</u>	<u>Occupational exposure limits</u>
dipropylene glycol methyl ether	<b>EU OEL (Europe, 2/2006). Skin Notes: Indicative</b> 8 hours: 308 mg/m <sup>3</sup> 8 hour(s). 8 hours: 50 ppm 8 hour(s).
propan-2-ol	<b>ACGIH TLV (United States, 1/2006). Notes: Refers to Appendix A -- Carcinogens. ACGIH 2003 Adoption</b> STEL: 400 ppm 15 minute(s). Form: All forms TWA: 200 ppm 8 hour(s). Form: All forms
2-butoxyethanol	<b>EU OEL (Europe, 2/2006). Skin Notes: Indicative</b> short term: 246 mg/m <sup>3</sup> 15 minute(s). short term: 50 ppm 15 minute(s). 8 hours: 98 mg/m <sup>3</sup> 8 hour(s). 8 hours: 20 ppm 8 hour(s).

**Personal protective equipment**

- Respiratory system** : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.
- Skin and body** : Personnel should wear antistatic clothing made of natural fibres or of high-temperature-resistant synthetic fibres.
- Hands**
- Gloves** : For prolonged or repeated handling, use the following type of gloves:
- Recommended: butyl rubber, foil, fluor rubber  
May be used: nitrile rubber, neoprene  
Not recommended: PVC

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

- Eyes** : Use safety eyewear designed to protect against splash of liquids.

**Environmental exposure controls**

Do not allow to enter drains or watercourses.

**9. Physical and chemical properties**

- Physical state** : Liquid.
- Flash point** : Closed cup: 60°C (140°F)
- Viscosity** : Kinematic: 1.848049 cm<sup>2</sup>/s (184.8049 cSt)
- Relative density** : 0.974

**10. Stability and reactivity**

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

**11. Toxicological information**

There is no data available on the preparation itself. The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

**Acute toxicity**

- Date of issue** : 15 June 2007
- Version number** : 7

Product/ingredient name	Result	Species	Dose	Exposure
dipropylene glycol methyl ether	LD50 Dermal	Rabbit	10 mL/kg	-
	LD50 Oral	Rat	5.5 ml/kg	-
	LD50 Oral	Rat	5400 µL/kg	-
2-butoxyethanol	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50	Rat	220 mg/kg	-
	Intraperitoneal			
	LD50 Intravenous	Rat	307 mg/kg	-
	LD50 Oral	Rat	470 mg/kg	-
	LD50 Oral	Rat	917 mg/kg	-
	LD50 Unreported	Rat	917 mg/kg	-
	TDL <sub>o</sub> Oral	Rat	500 mg/kg	-
	TDL <sub>o</sub> Unreported	Rat	250 mg/kg	-

**Conclusion/Summary** : Not available.

#### Chronic toxicity

**Conclusion/Summary** : Not available.

#### Carcinogenicity

**Conclusion/Summary** : Not available.

#### Mutagenicity

**Conclusion/Summary** : Not available.

#### Teratogenicity

**Conclusion/Summary** : Not available.

#### Reproductive toxicity

**Conclusion/Summary** : Not available.

## 12. Ecological information

There is no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

#### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
2-butoxyethanol	Mortality	Acute LC50 1490 mg/L	Fish	96 hours

**Conclusion/Summary** : Not available.

#### Biodegradability

**Conclusion/Summary** : Not available.

## 13. Disposal considerations

Do not allow to enter drains or watercourses.  
Dispose of according to all federal, state and local applicable regulations.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

## 14. Transport information

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

#### Land - road/railway

<b>UN number</b>	: UN1263
<b>Transport document name</b>	: PAINT RELATED MATERIAL
<b>ADR/RID Class</b>	: 3
<b>Packing group</b>	: III

ADR/RID Label

:

Sea

UN number

: UN1263

Proper shipping name

: PAINT RELATED MATERIAL

Special provisions

: Not available.

IMDG Class

: 3

Packing group

: III

IMDG Label

:



Marine pollutant

: No.

Emergency schedules  
(EmS)

: F-E, S-E

Air

UN number

: UN1263

Proper shipping name

: PAINT RELATED MATERIAL

Special provisions

: Not available.

ICAO/IATA Classification

: 3

Packing group

: III

The "viscosity exemption" provisions do not apply to air transport.

ICAO/IATA label

:

Inland waterways

UN number

: UN1263

Proper shipping name

: PAINT RELATED MATERIAL

ADNR Classification

: 3

Packing group

: III

ADNR Label

:



## 15. Regulatory information

EU regulations

: The product is determined as not being dangerous according to the requirements of the DPD.

Risk phrases

: This product is not classified according to EU legislation.

Additional warning phrases

: Safety data sheet available for professional user on request.

Industrial use

: The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

## 16. Other information

**CEPE Classification** : 9  
**Full text of R-phrases referred to in sections 2 and 3 - Europe** : R11- Highly flammable.  
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.  
R36- Irritating to eyes.  
R36/38- Irritating to eyes and skin.  
R67- Vapours may cause drowsiness and dizziness.

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

**Date of issue/Date of revision** : 6/15/2007.

Indicates information that has changed from previously issued version.

### Notice to reader

#### **FOR PROFESSIONAL USE ONLY**

**IMPORTANT NOTE** The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to Akzo Nobel.

#### **Head Office**

Akzo Nobel Car Refinishes bv, Rijksweg 31 2171 AJ Sassenheim. <http://www.sikkenscr.com>