



SAFETY DATA SHEET

ACRYL-KLARLACK MS

Page 1

Issued: 23.11.2007

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ACRYL-KLARLACK MS

Product code: I1

Company name: AIRO CHEMIE

A. Schmiemann GmBH & Co KG

Carl-Leverkus Str. 27

D - 40736 Lagenfeld

Deutschland

Tel: [49] 02173 8538-0

Fax: [49] 02173 8538-60

Emergency tel: 02173-8538-0

Email: j.bujnowski@airo-chemie.com

2. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation, in contact with skin and if swallowed. Irritating to eyes.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Harmful: may cause lung damage if swallowed. Possible risk of irreversible effects.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: 2-METHOXY-1-METHYLETHYL ACETATE 20-30%

EINECS: 203-603-9 CAS: 108-65-6

[-] R10; [Xi] R36

- LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM),

LIGHT AROM. 10-20%

EINECS: 265-199-0 CAS: 64742-95-6

[-] R10; [Xi] R37; [N] R51/53; [Xn] R65

- N-BUTYL ACETATE 1-10%

EINECS: 204-658-1 CAS: 123-86-4

[-] R10; [-] R66; [-] R67

- XYLENE 1-10%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- 2-METHOXYANILINE 1-10%

EINECS: 201-963-1 CAS: 90-04-0

[T] R45; [T] R23/24/25; [Xn] R68

- XYLENOL <1%

EINECS: 215-089-3 CAS: 1300-71-6

[T] R24/25; [C] R34; [N] R51/53

[cont...]

4. FIRST AID MEASURES (SYMPTOMS)

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and redness. The eyes may water profusely.
- Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.
- Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.
- Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

7. HANDLING AND STORAGE

- Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.
- Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Coated steel.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: N-BUTYL ACETATE

WEL (8 hr TWA): 724 mg/m³ WEL (15 min STEL): 966 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Solubility in water: Not miscible

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Viscosity value: 70 sec.

Boiling point/range°C: 137

Melting point/range°C: n.v.

Flammability limits %: lower: 1

upper: 7,6

Flash point°C: > 25

Part.coeff. n-octanol/water: n.v.

Autoflammability°C: 465

Vapour pressure: 7-8 mbar

Relative density: 0,977 g/cm³

pH: n.a.

VOC g/l: 508 g/l

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: 2-METHOXY-1-METHYLETHYL ACETATE

IPR MUS LD50 750 mg/kg

ORL RAT LD50 8532 mg/kg

SAFETY DATA SHEET

ACRYL-KLARLACK MS

- LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.
ORL RAT LD50 8400 mg/kg
- N-BUTYL ACETATE
ORL MUS LD50 6 gm/kg
ORL RAT LD50 10768 mg/kg
- XYLENE
ORL MUS LD50 2119 mg/kg
ORL RAT LD50 4300 mg/kg
SCU RAT LD50 1700 mg/kg
- 2-METHOXYANILINE
ORL MUS LD50 1400 mg/kg
ORL RAT LD50 1150 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

Waste code number: 08 01 11

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION**ADR / RID**

UN no: 1263

ADR Class: 3

Packing group: III

Classification code: F1

Shipping name: PAINT

Labelling: 3

Hazard ID no: 30



IMDG / IMO

UN no: 1263 **Class:** 3
Packing group: III **EmS:** F-E,S-E*
Marine pollutant: .
Labelling: 3

IATA / ICAO

UN no: 1263 **Class:** 3
Packing group: III
Packing instructions: 309(P&CA); 310(CAO)
Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.
R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.
R36: Irritating to eyes.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R68: Possible risk of irreversible effects.

Safety phrases: S36/37: Wear suitable protective clothing and gloves.
S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Seveso II guideline: Yes

Water hazard class: 2 Classification by VwVwS

Air emission directive: Class: II Item no: 5.2.5 Amount m%: 12,5-20

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.3: R10: Flammable.
R36: Irritating to eyes.
R37: Irritating to respiratory system.

SAFETY DATA SHEET

ACRYL-KLARLACK MS

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R45: May cause cancer.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R68: Possible risk of irreversible effects.

R24/25: Toxic in contact with skin and if swallowed.

R34: Causes burns.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.