

# U-POL

## PRODUCTS

### PRODUCT SAFETY DATA SHEET

---

**COMMERCIAL PRODUCT NAME:** UPOL CUSTOM CAN AEROSOL

**PREPARATION:** PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

**ADDRESS:** Denington Industrial Estate,  
Denington Road,  
Wellingborough,  
Northants NN8 2QP  
United Kingdom

**EMERGENCY TELEPHONE NO:-** **44-(0)1933-230310**

**FAX NO:-** 44-(0)1933-230351

#### **COMPOSITION/INFORMATION ON INGREDIENTS**

<b><u>COMPONENT</u></b>	<b><u>CAS NO.</u></b>	<b><u>LEVEL</u></b>	<b><u>SYMBOL</u></b>	<b><u>RISK</u></b>
ACETONE	67-64-1	10 - 25%	F - Highly Flammable	R11
DIMETHYL ETHER	115-10-6	50 - 75%	F+ - Extremely flammable.	R12

#### **HAZARDS IDENTIFICATION**

**INHALATION:** May cause drowsiness and irritation of respiratory tract.

**SKIN:** May cause irritation on prolonged contact, which can lead to dermatitis.

**EYES:** Irritation and soreness.

**INGESTION:** Sore throat, stomachache, nausea, but unlikely to be ingested.

#### **FIRST AID MEASURES**

**INHALATION:** Move affected person to the fresh air without delay. If drowsiness persists seek medical attention.

**SKIN CONTACT:** Wash affected area with warm soapy water. Do not use solvents.

**EYE CONTACT:** Irrigate with copious quantities of water and seek medical attention immediately.

**INGESTION:** Do not induce vomiting, drink plenty of water and seek medical attention.

## **FIRE FIGHTING MEASURES**

Fight fires with CO<sub>2</sub>, dry powder, or chemical foam. Do not use water jets. Burning material emits toxic fumes and smoke, so avoid inhalation of burning products.

## **ACCIDENTAL RELEASE MEASURES**

The product will readily flow. Contain and collect any spillage with sand or earth. Keep product away from drains. Avoid sources of ignition. Dispose of in accordance with the requirements of the Environmental Protection Act.

## **HANDLING AND STORAGE**

### **HANDLING:**

Keep away from heat. Keep away from sources of ignition. Avoid contact with skin and eyes. Use only in well ventilated areas, and for extensive spraying, in a suitable booth.

### **STORAGE:**

Store below 25°C in a dry well ventilated space in original containers. Keep away from sources of heat.

## **EXPOSURE CONTROLS/PERSONAL PROTECTION**

A good standard of personal and industrial hygiene should be maintained at all times. Persons who suffer from skin complaints or other allergic effects should not work with the product.

<b>OEL (UK)</b>	<b>Component</b>	<b>8 HR TWA</b>	<b>15 mins STEL</b>
	Acetone	750 ppm	1500 ppm
	Dimethyl Ether	400 ppm	500 ppm

### **EYE PROTECTION:**

Not necessary.

### **PROTECTIVE CLOTHING:**

Recommended.

### **RESPIRATORY PROTECTION:**

Suitable respiratory protection necessary, when spraying in areas of poor ventilation.

### **SKIN PROTECTION:**

Barrier cream recommended.

## **PHYSICAL AND CHEMICAL PROPERTIES**

### **APPEARANCE:**

Colourless liquid.

### **ODOUR:**

Characteristic.

### **DENSITY:**

N/A.

### **FLASH POINT:**

Approx. -40°C.

### **AUTOFLAMMABILITY TEMPERATURE:**

Unknown.

### **EXPLOSIVE LIMITS:**

Lower 3.0%. Upper 18.6% (DME).

### **VOLATILE CONTENT:**

Approx. 100%.

### **SOLUBILITY:**

Immiscible with water.

### **VISCOSITY:**

N/A.

## **STABILITY AND REACTIVITY**

Stable under normal conditions. Avoid naked flames. Heat increase may be sufficient to raise the temperature above the product flash point. Thermal decomposition can give rise to acrid fumes.

## **TOXICOLOGICAL INFORMATION**

For Acetone, the following values have been reported:-

An oral LD50 in rats of 5.8g/Kg.

LC50 in rats of 50mg/L.

For Dimethyl Ether, the following values have been reported:-

LC50 in rats of 164mg/L.

## **ECOLOGICAL INFORMATION**

### **Marine pollutant and non biodegradeable.**

Paints are low viscosity compositions which lose solvents by evaporation, leaving a relatively inert residue which will not degrade significantly.

## **DISPOSAL CONSIDERATIONS**

The material and any contaminated container should be disposed of in accordance with the Environmental Protection Act.

## **TRANSPORT INFORMATION**

<b>SHIPPING NAME:</b>	AEROSOLS.
<b>UNITED NATION NO:</b>	UN 1950.
<b>CLASS NO:</b>	2.1
<b>HARMONISED SYSTEMS NO:</b>	320890 91 5.
<b>PACKING GROUP:</b>	Not allocated.

Complies with The Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations.

For current International Maritime Dangerous Goods Declaration, please contact our Export Department  
Telephone No: 44-(0)20 84925950.

## **REGULATORY INFORMATION**

**CONTAINS:**

Mixture of solvents.

**SYMBOL:**

Xi      Irritant.  
F+      Extremely flammable.

**RISK PHRASES:**

R36      Irritating to the eyes.

**SAFETY PHRASES:**

S2      Keep out of reach of children.  
S23      Do not breathe vapour/spray.  
S25      Avoid contact with the eyes.  
S51      Use only in well ventilated areas.

Pressurised container, protect from sunlight and do not expose to temperatures exceeding 50°C.  
Do not pierce or burn even after use.  
Do not spray on a naked flame or any incandescent material.

The following warning may be applicable depending on the type of paint added: Contains toluene and/or Xylene - Harmful.

## **FURTHER INFORMATION**

Reference should be made to the following official publications:-

EH40, COSHH Regulations, Environmental Protection Act.

**ISSUE NUMBER: 0001**

**ISSUE DATE: 23.11.01**