

U-POL™

SAFETY DATA SHEET

DEEPCOAT

Page 1

Issued: 03/01/2005

Revision No: 5

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: DEEPCOAT

Product code: DEEP/2.5

Use / description of product: PAINT PRODUCT CONTAINING NITOCCELLULOSE AND A MIXTURE OF SOLVENTS

Company name: U-Pol Products

Denington Industrial Estate

Denington Road

Wellingborough

Northants

NN8 2QP

United Kingdom

Tel: 44-(0)-1933 230300

Fax: 44-(0)-1933 230351

Emergency tel: 44-(0)-1933 230310

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: XYLENE 10-30%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- N-BUTYL ACETATE 1-10%

EINECS: 204-658-1 CAS: 123-86-4

[-] R10; [Xi] R66; [-] R67

- ISOBUTYL ACETATE 10-30%

EINECS: 203-745-1 CAS: 110-19-0

[F] R11; [Xi] R66

- ETHYL METHYL KETONE 1-10%

EINECS: 201-159-0 CAS: 78-93-3

[F] R11; [Xi] R36; [Xi] R66; [-] R67

[cont...]

SAFETY DATA SHEET

DEEPCOAT

3. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation and in contact with skin.

Other hazards: May cause fire. May cause sensitisation by skin contact.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and pain.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Workplace exposure limits**

WEL (8 hr exposure limit): 50 ppm

WEL (15 min exposure limit): 100 ppm

Respirable dust

WEL (8 hr exposure limit): 1 mg/m³

SAFETY DATA SHEET

DEEPCOAT

Hazardous ingredients: XYLENETWA 220 mg/m³ STEL 441 mg/m³

• N-BUTYL ACETATE

TWA 724 mg/m³ STEL 966 mg/m³

• ISOBUTYL ACETATE

TWA 724 mg/m³ STEL 903 mg/m³

• ETHYL METHYL KETONE

TWA 600 mg/m³ STEL 899 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Compressed airline breathing apparatus (EN139).

Hand protection: Nitrile gloves.

Eye protection: Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Yellow-green

Odour: Alcoholic

Evaporation rate: Moderate

Solubility in water: Miscible

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Viscosity value: 550 cps

Flammability limits %: lower: 2.0

upper: 15.0

Flash point°C: 16

Autoflammability°C: 423

Relative density: 1.10

VOC g/l: 494

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Sources of ignition.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION**Hazardous ingredients:** XYLENE

ORL MUS LD50 2119 mg/kg

SAFETY DATA SHEET

DEEPCOAT

ORL RAT LD50 4300 mg/kg

SCU RAT LD50 1700 mg/kg

• N-BUTYL ACETATE

ORL MUS LD50 6 gm/kg

ORL RAT LD50 10768 mg/kg

• ISOBUTYL ACETATE

ORL RAT LD50 13400 mg/kg

ORL RBT LD50 4763 mg/kg

SKN RBT LD50 >17400 mg/kg

Chronic toxicity: May cause sensitisation by skin contact.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Heavier than water.**Persistence and degradability:** Not biodegradable.**Bioaccumulative potential:** No data available.**Other adverse effects:** Very toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** D10 Incineration on land.

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1263**ADR Class:** 3**Packing group:** II**Classification code:** F1**Shipping name:** PAINT**Labelling:** 3**Hazard ID no:** 33**IMDG / IMO****UN no:** 1263**Class:** 3**Packing group:** II**EmS:** F-E,S-E

SAFETY DATA SHEET

DEEPCOAT

Marine pollutant: .**Labelling:** 3**IATA / ICAO****UN no:** 1263**Class:** 3**Packing group:** II**Packing instructions:** 305(P&CA); 307(CAO)**Labelling:** 3**15. REGULATORY INFORMATION****Hazard symbols:** Highly flammable.

Harmful.

**Risk phrases:** R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

Safety phrases: S3: Keep in a cool place.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour/spray

S36/37: Wear suitable protective clothing and gloves.

VbF: AII**Water hazard class:** 1

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION**Other information:** This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.**Risk phrases used in s.2:** R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R11: Highly flammable.

R36: Irritating to eyes.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.