

U-POL

PRODUCTS

PRODUCT SAFETY DATA SHEET

COMMERCIAL PRODUCT NAME: UPOL ANTI-SILICONE AEROSOL

PREPARATION: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

ADDRESS: Denington Industrial Estate,
Denington Road,
Wellingborough,
Northants NN8 2QP
United Kingdom

EMERGENCY TELEPHONE NO:- **44-(0)1933-230310**

FAX NO:- 44-(0)1933-230351

COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>LEVEL</u>	<u>SYMBOL</u>	<u>RISK</u>
PETROLEUM NAPHTHA	64741-84-0	20 - 30%	Xn - Harmful.	R65
PETROLEUM NAPHTHA	64742-88-7	20 - 30%	F - Highly flammable.	R11
			Xn - Harmful.	R65
				R10
BUTANE	106-97-8	10 - 25%	F+ - Extremely flammable.	R12
PROPANE	74-98-6	10 - 25%	F+ - Extremely flammable.	R12

HAZARDS IDENTIFICATION

INHALATION: May cause drowsiness and irritation of respiratory tract.

SKIN: May cause irritation on prolonged contact, which can lead to dermatitis.

EYES: Irritation and soreness.

INGESTION: Sore throat, stomachache, nausea, but unlikely to be ingested.

FIRST AID MEASURES

INHALATION: Move affected person to the fresh air without delay. If drowsiness persists seek medical attention.

SKIN CONTACT: Wash affected area with warm soapy water. Do not use solvents.

EYE CONTACT: Irrigate with copious quantities of water and seek medical attention immediately.

INGESTION: Do not induce vomiting, drink plenty of water and seek medical attention.

FIRE FIGHTING MEASURES

Fight fires with CO₂, dry powder, or chemical foam. Do not use water jets. Burning material emits toxic fumes and smoke, so avoid inhalation of burning products.

ACCIDENTAL RELEASE MEASURES

The product will readily flow. Contain and collect any spillage with sand or earth. Keep product away from drains. Avoid sources of ignition. Dispose of in accordance with the requirements of the Environmental Protection Act.

HANDLING AND STORAGE

HANDLING:

Keep away from heat. Keep away from sources of ignition. Avoid contact with skin and eyes. Use only in well ventilated areas, and for extensive spraying, in a suitable booth.

STORAGE:

Store below 25°C in a dry well ventilated space in original containers. Keep away from sources of heat.

EXPOSURE CONTROLS/PERSONAL PROTECTION *

A good standard of personal and industrial hygiene should be maintained at all times. Persons who suffer from skin complaints or other allergic effects should not work with the product.

OEL (UK)	Component	8 HR TWA	15 mins STEL
	Petroleum Naphtha	250 mg/m ³	300 mg/m ³
	Butane	600 ppm	750 ppm

EYE PROTECTION:

Not necessary.

PROTECTIVE CLOTHING:

Recommended.

RESPIRATORY PROTECTION:

Suitable respiratory protection necessary, when spraying in areas of poor ventilation.

SKIN PROTECTION:

Barrier cream recommended.

PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

Clear liquid.

ODOUR:

Characteristic of solvents.

DENSITY:

N/A.

FLASH POINT:

- 40°C.

AUTOFLAMMABILITY TEMPERATURE:

> 250°C

EXPLOSIVE LIMITS:

Lower 0.8%. Upper 9.0% .

VOLATILE CONTENT:

Approx. 100%.

SOLUBILITY:

Partially soluble in water.

VISCOSITY:

N/A.

STABILITY AND REACTIVITY

Stable under normal conditions. Avoid named flames. Heat increase may be sufficient to raise the temperature above the product flash point. Thermal decomposition can give rise to acrid fumes.

TOXICOLOGICAL INFORMATION

None quoted.

ECOLOGICAL INFORMATION

Marine pollutant and non biodegradable.

Paints are low viscosity compositions which lose solvents by evaporation, leaving a relatively inert residue which will not degrade significantly.

DISPOSAL CONSIDERATIONS

The material and any contaminated container should be disposed of in accordance with the Environmental Protection Act.

TRANSPORT INFORMATION

SHIPPING NAME:	AEROSOLS.
UNITED NATION NO:	UN 1950.
CLASS NO:	2.1
HARMONISED SYSTEMS NO:	320890 91 5.
PACKING GROUP:	Not allocated.

Complies with The Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations.

For current International Maritime Dangerous Goods Declaration, please contact our Export Department
Telephone No: 44-(0)20 8492 5950.

REGULATORY INFORMATION

CONTAINS:

Mixture of solvents.

SYMBOL:

Xn Harmful.
F+ Extremely flammable.

RISK PHRASES:

R65 Harmful. May cause lung damage if swallowed.

SAFETY PHRASES:

S16 Keep away from sources of ignition - No smoking.
S23 Do not breathe vapour/spray.
S24/25 Avoid contact with skin and eyes.
S51 Use only in well ventilated areas.

Pressurised container, protect from sunlight and do not expose to temperatures exceeding 50°C.
Do not pierce or burn even after use.
Do not spray on a naked flame or any incandescent material.

FURTHER INFORMATION

Reference should be made to the following official publications:-

EH40, COSHH Regulations, Environmental Protection Act.

ISSUE NUMBER: 0002
(*Denotes changes from previous issue)

ISSUE DATE: 11.11.02