

U-POL™

SAFETY DATA SHEET 2K SYSTEM 20 COLOUR MATCH PRIMER

Page 1
Issued: 03/01/2005
Revision No: 3

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 2K SYSTEM 20 COLOUR MATCH PRIMER

Product code: S2022

Use / description of product: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

Company name: U-Pol Products
Denington Industrial Estate
Denington Road
Wellingborough
Northants
NN8 2QP
United Kingdom
Tel: 44-(0)-1933 230300
Fax: 44-(0)-1933 230351
Emergency tel: 44-(0)-1933 230310

2. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** XYLENE 1-10%
EINECS: 215-535-7 CAS: 1330-20-7
[-] R10; [Xn] R20/21; [Xi] R38
- N-BUTYL ACETATE 10-30%
EINECS: 204-658-1 CAS: 123-86-4
[-] R10; [Xi] R66; [-] R67
 - LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM),
LIGHT AROM. 1-10%
EINECS: 265-199-0 CAS: 64742-95-6
[F+] R12; [Xi] R38; [N] R51/53; [Xn] R65

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

[cont...]

SAFETY DATA SHEET

2K SYSTEM 20 COLOUR MATCH PRIMER

4. FIRST AID MEASURES (SYMPTOMS)

- Skin contact:** There may be irritation and redness at the site of contact.
- Eye contact:** There may be irritation and pain.
- Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.
- Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

- Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.
- Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.
- Ingestion:** Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.
- Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

- Extinguishing media:** Carbon dioxide. Dry chemical powder. Alcohol or polymer foam. Do not use water.
- Exposure hazards:** Flammable. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.
- Protection of fire-fighters:** Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions:** Refer to section 8 of SDS for personal protection details.
- Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.
- Clean-up procedures:** Absorb into dry earth or sand. Wash the spillage site with large amounts of water. Refer to section 13 of SDS for suitable method of disposal.

7. HANDLING AND STORAGE

- Handling requirements:** Ensure there is sufficient ventilation of the area. Smoking is forbidden.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition. Keep container tightly closed.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

- WEL (8 hr exposure limit):** 50 ppm
- WEL (15 min exposure limit):** 100ppm

Respirable dust

- WEL (8 hr exposure limit):** 1 mg/m³

Hazardous ingredients:

- XYLENE
TWA 220 mg/m³ STEL 441 mg/m³
- N-BUTYL ACETATE
TWA 724 mg/m³ STEL 966 mg/m³

SAFETY DATA SHEET

2K SYSTEM 20 COLOUR MATCH PRIMER

- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Compressed airline breathing apparatus (EN139).
- Hand protection:** Nitrile gloves.
- Eye protection:** Face-shield.
- Skin protection:** Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Liquid
- Colour:** Pale grey
- Odour:** Aromatic
- Evaporation rate:** Moderate
- Oxidising:** Non-oxidising (by EC criteria)
- Solubility in water:** Insoluble
- Also soluble in:** Most organic solvents.
- Viscosity:** Viscous
- Viscosity value:** 6000cps
- Flammability limits %: lower:** 1.0
- upper:** 6.6
- Flash point°C:** 24
- Autoflammability°C:** 490
- Relative density:** 1.6
- VOC g/l:** 417

10. STABILITY AND REACTIVITY

- Stability:** Stable under normal conditions.
- Conditions to avoid:** Heat. Sources of ignition.
- Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

- Hazardous ingredients:** XYLENE
- ORL MUS LD50 2119 mg/kg
- ORL RAT LD50 4300 mg/kg
- SCU RAT LD50 1700 mg/kg
- N-BUTYL ACETATE
- ORL MUS LD50 6 gm/kg
- ORL RAT LD50 10768 mg/kg
- LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.
- ORL RAT LD50 8400 mg/kg

SAFETY DATA SHEET

2K SYSTEM 20 COLOUR MATCH PRIMER

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Volatile. Heavier than water.

Persistence and degradability: Not biodegradable.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D10 Incineration on land.

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1263

ADR Class: 3

Packing group: III

Classification code: F1

Shipping name: PAINT RELATED MATERIAL

Labelling: 3

Hazard ID no: 30



IMDG / IMO

UN no: 1263

Class: 3

Packing group: III

EmS: F-E,S-E

Marine pollutant: .

Labelling: 3

IATA / ICAO

UN no: 1263

Class: 3

Packing group: III

Packing instructions: 309(P&CA); 310(CAO)

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: No significant hazard.

Risk phrases: R10: Flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY DATA SHEET
2K SYSTEM 20 COLOUR MATCH PRIMER

Safety phrases: S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe vapour/spray
S36/37: Wear suitable protective clothing and gloves.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Other information: This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.

Risk phrases used in s.2: R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.
R12: Extremely flammable.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.