

U-POL™

SAFETY DATA SHEET

2K SYSTEM 20 FAST MULTIFUNCTION THINNERS

Page 1

Issued: 03/01/2005

Revision No: 2

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: 2K SYSTEM 20 FAST MULTIFUNCTION THINNERS

Product code: S2044

Use / description of product: PAINT PRODUCT CONTAINING MIXTURE OF SOLVENTS

Company name: U-Pol Products

Denington Industrial Estate

Denington Road

Wellingborough

Northants

NN8 2QP

United Kingdom

Tel: 44-(0)-1933 230300

Fax: 44-(0)-1933 230351

Emergency tel: 44-(0)-1933 230310

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: N-BUTYL ACETATE 50-70%

EINECS: 204-658-1 CAS: 123-86-4

[-] R10; [Xi] R66; [-] R67

- 2-METHOXY-1-METHYLETHYL ACETATE 10-30%

EINECS: 203-603-9 CAS: 108-65-6

[-] R10; [Xi] R36

- XYLENE 10-30%

EINECS: 215-535-7 CAS: 1330-20-7

[-] R10; [Xn] R20/21; [Xi] R38

- 2-BUTOXYETHYL ACETATE 1-10%

EINECS: 203-933-3 CAS: 112-07-2

[Xn] R20/21

[cont...]

SAFETY DATA SHEET

2K SYSTEM 20 FAST MULTIFUNCTION THINNERS

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful by inhalation and in contact with skin. Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. Wash out mouth with water. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Carbon dioxide. Alcohol or polymer foam. Dry chemical powder. Do not use water.

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Protection of fire-fighters: Wear self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Alert the neighbourhood to the presence of fumes or gas.

Clean-up procedures: Absorb into dry earth or sand. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

WEL (8 hr exposure limit): 50 ppm

WEL (15 min exposure limit): 100 ppm

Hazardous ingredients: N-BUTYL ACETATE

TWA 724 mg/m³ STEL 966 mg/m³

SAFETY DATA SHEET

2K SYSTEM 20 FAST MULTIFUNCTION THINNERS

- 2-METHOXY-1-METHYLETHYL ACETATE
TWA 274 mg/m³ STEL 822 mg/m³
- XYLENE
TWA 220 mg/m³ STEL 441 mg/m³
- 2-BUTOXYETHYL ACETATE
TWA 130 mg/m³ STEL 520 mg/m³

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Compressed airline breathing apparatus (EN139).

Hand protection: Nitrile gloves.

Eye protection: Face-shield.

Skin protection: Protective clothing with elasticated cuffs and closed neck.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Aromatic

Evaporation rate: Moderate

Solubility in water: Miscible

Viscosity: Non-viscous

Flammability limits %: lower: 1.0

upper: 6.6

Flash point°C: 24

Autoflammability°C: 490

Relative density: 0.9

VOC g/l: 900

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Heat. Direct sunlight. Sources of ignition.

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

11. TOXICOLOGICAL INFORMATION

Hazardous ingredients: N-BUTYL ACETATE

ORL MUS LD50 6 gm/kg

ORL RAT LD50 10768 mg/kg

- 2-METHOXY-1-METHYLETHYL ACETATE

IPR MUS LD50 750 mg/kg

ORL RAT LD50 8532 mg/kg

- XYLENE

SAFETY DATA SHEET
2K SYSTEM 20 FAST MULTIFUNCTION THINNERS

- ORL MUS LD50 2119 mg/kg
- ORL RAT LD50 4300 mg/kg
- SCU RAT LD50 1700 mg/kg
- 2-BUTOXYETHYL ACETATE
- ORL MUS LD50 3200 mg/kg
- ORL RAT LD50 2400 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Volatile. Floats on water.

Persistence and degradability: Only slightly biodegradable.

Bioaccumulative potential: No data available.

Other adverse effects: No data available.

13. DISPOSAL CONSIDERATIONS

Disposal operations: D10 Incineration on land.
R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

| | |
|--|--------------------------------|
| UN no: 1263 | ADR Class: 3 |
| Packing group: III | Classification code: F1 |
| Shipping name: PAINT RELATED MATERIAL | |
| Labelling: 3 | Hazard ID no: 30 |



IMDG / IMO

| | |
|----------------------------|---------------------|
| UN no: 1263 | Class: 3 |
| Packing group: III | EmS: F-E,S-E |
| Marine pollutant: . | Labelling: 3 |

IATA / ICAO

| | |
|---------------------------|--|
| UN no: 1263 | Class: 3 |
| Packing group: III | Packing instructions: 309(P&CA); 310(CAO) |

Labelling: 3**15. REGULATORY INFORMATION****Hazard symbols:** Harmful.**Risk phrases:** R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe vapour/spray

S36/37: Wear suitable protective clothing and gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

VbF: AII**Water hazard class:** 1 Classification by VwVwS**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.**16. OTHER INFORMATION****Other information:** This safety data sheet is prepared in accordance with EC Directive 2001/58/EC.**Risk phrases used in s.2:** R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R36: Irritating to eyes.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.